



TERMINALS & SPLICES

## MOTOR TERMINAL HOUSINGS



TE CONNECTIVITY (TE)

### .250 S CIR FAST HSG NAT

FASTON | FASTON Terminals and Housings

1-480416-0

TE Internal Number: 1-480416-0

Always EU RoHS/ELV Compliant

Product Type **Terminal Housing**

Number of Circuits **1**

Terminal Orientation **Straight**

Wire Insulation Diameter (Max) **5.08 mm [ .2 in ]**

Material **Nylon 6/6**

✓ Active

↓ **PRODUCT DRAWING**  
English

↓ **3D PDF**



### Product Drawings

**HOUSING, RECEPTACLE, FASTON, 6.35 [.250] SERIES**

PDF  
English

### CAD Files

**Customer View Model**

3D\_STP.ZIP  
English

**Customer View Model**

3D\_IGS.ZIP  
English

**Customer View Model**

2D\_DXF.ZIP  
English

**3D PDF**

PDF  
3D

**Customer View Model**

3D\_IGS.ZIP  
English

**Customer View Model**

3D\_STP.ZIP  
English

[Customer View Model](#)

2D\_DXF.ZIP  
English

[3D PDF](#)

PDF  
English

---

Catalog Pages/Data Sheets

[FASTON Housings](#)

PDF  
English

---

Product Environmental Compliance

TE Material Declaration

[MD\\_1-480416-0\\_02122016849\\_dmtec](#)

PDF  
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

---

Product Type Features

Product Type

**Terminal Housing**

FASTON

**Yes**

Connector Style

**Receptacle**

Style Code

**B**

---

Configuration Features

Number of Circuits

**1**

Number of Positions

**1**

---

Body Features

Material

**Nylon 6/6**

Color

**Natural**

---

Contact Features

Terminal Orientation

**Straight**

Accepts Terminal Style

**Receptacle**

---

Housing Features

Housing Material

**Nylon 6/6**

---

Dimensions

Wire Insulation Diameter (Max)

**5.08 mm [ .2 in ]**

Length

**23.37 mm [ .92 in ]**

---

Industry Standards

UL Flammability Rating

**UL 94V-2**

---

Packaging Features

Packaging Method

**Package**

Packaging Quantity

**1**

[VIEW ALL PRODUCT COMPLIANCE](#)

