



MOTOR TERMINAL HOUSINGS



TE CONNECTIVITY (TE)

110 S CIR FAST HSG NAT N

[FASTON](#) | [FASTON Terminals and Housings](#)

1-480417-0

TE Internal Number: 1-480417-0

Always EU RoHS/ELV Compliant

Product Type **Terminal Housing**

Number of Circuits **1**

Wire Insulation Diameter (Max) (mm) **3.81**

Wire Insulation Diameter (Max) (in) **.15, .18**

Material **Nylon**

Color **Natural**

✓ Active

[PRODUCT DRAWING](#)
English

[3D PDF](#)

Product Drawings

[HOUSING, RECEPTACLE, FASTON, .110 SERIES](#)

PDF
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[3D PDF](#)

PDF
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Catalog Pages/Data Sheets

[FASTON Housings](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_1-480417-0_0505201544_dmtec](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Product Type

Terminal Housing

FASTON

Yes

Connector Style

Receptacle

	Connector Style	Receptacle
	Style Code	E
Configuration Features	Number of Circuits	1
	Number of Positions	1
Body Features	Material	Nylon
	Color	Natural
Contact Features	Accepts Terminal Style	Receptacle
Mechanical Attachment	Polarized	No
Housing Features	Housing Material	Nylon
Dimensions	Wire Insulation Diameter (Max) (mm)	3.81
	Wire Insulation Diameter (Max) (in)	.15, .18
	Length	20.066 mm [.79 in]
Industry Standards	UL Flammability Rating	UL 94V-2
Packaging Features	Packaging Method	Package
	Packaging Quantity	1
Product Compliance	Statement of Compliance PDF VIEW ALL PRODUCT COMPLIANCE	