



1-5332095-9 Product Details

[Share](#) [Print](#) [Email](#)


1-5332095-9

TE Internal Number: 1-5332095-9

Active

View 3D PDF

Discrete Sockets

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Mini-Spring Socket Product Line
- Board-to-Board, Wire-to-Board
- Applies To Wire/Cable, Applies To Printed Circuit Board
- Contact - Rated Current = 5 A
- Wire/Cable Size = .081 - .162 mm²

[View all Features](#)

Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

[Add to My Part List](#) [Request Sample](#) [Find Similar Products](#) [Buy Product](#)

Documentation & Additional Information

Product Drawings:

- [MINIATURE SPRING SOCKET ASSEMBLY SERIES 1](#) (PDF, English)

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files: (CAD Format & Compression Information)

- [2D Drawing](#) (DXF, Version 0)
- [3D Model](#) (IGES, Version 0)
- [3D Model](#) (STEP, Version 0)

[List all Documents](#)

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Line = Mini-Spring Socket
- [Sleeve Style](#) = Knockout Bottom
- [Sealant](#) = Without
- Wire/Cable Type = Discrete Wire
- Product Series = 3
- Profile = Zero

Electrical Characteristics:

- Contact - Rated Current (A) = 5

Termination Features:

- Wire/Cable Size (mm²) = 0.081 - 0.162
- Wire/Cable Size (AWG) = 25 - 28
- [Insertion Method](#) = Hand/Semi-Automatic
- Termination Method to Wire/Cable = Solder
- Termination Method to PC Board = Through Hole - Press Fit

Dimensions:

- [Socket Length \(mm \[in\]\)](#) = 4.52 [0.178]
- Recommended Hole Size (mm [in]) = 1.04 [0.041]
- PCB Thickness, Recommended (mm [in]) = 0.79 - 3.18 [0.031 - 0.125]

Body Features:

- [Mating Pin Dia. Range \(mm \[in\]\)](#) = 0.33 - 0.51 [0.013 - 0.020]

Contact Features:

- [Contact Spring Plating](#) = Gold (30)
- Contact Plating, Mating Area, Material = Gold (30)
- Contact Plating, Mating Area, Thickness (µm [µin]) = 0.00076 [0.03]
- Contact Type = Socket
- Contact Base Material = Beryllium Copper

Industry Standards:

- Government/Industry Qualification = No
- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 260°C, Wave solder capable to 240°C, Wave solder capable to 265°C, Reflow solder capable to 245°C, Reflow solder capable to 260°C, Pin-in-Paste capable to 245°C, Pin-in-Paste capable to 260°C
- RoHS/ELV Compliance History = Always was RoHS compliant

Environmental:

- Operating Temperature (°C [°F]) = -65 - +126 [-85 - +258]

Conditions for Usage:

- Applies To = Wire/Cable, Printed Circuit Board

Operation/Application:

- Application Use = Board-to-Board, Wire-to-Board
- Contact Transmits (Typical Application) = Signal (Data)/Power
- Application = Production

Feedback

- [Sleeve Material Plating](#) = Tin
- Wire Type = Solid
- Sleeve Material = Copper
- Spring Material = Beryllium Copper

Packaging Features:

- Packaging Method = Loose Piece
- Packaging Quantity = 2,000/Bag

Other:

- Brand = AMP

Corporate Information

- [About TE](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)
- [Terms & Conditions](#)
- [Privacy Policy](#)
- [AODA Accessibility Policy](#)
- [AODA Multi-Year Accessibility Plan](#)

Quick Links

- [Distributor Inventory](#)
- [Product Cross Reference](#)
- [Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

Customer Support

- [Email or Chat With Us](#)
- [Find a Phone Number](#)
- [Knowledge Base](#)
- [Manage Your Account](#)

Keep Me Informed