

PCB D-SUB CONNECTORS







PRODUCT DRAWING



3D PDF

TE CONNECTIVITY (TE)

09 RCPT SP/FMS SCRLK

AMPLIMITE | SP , Standard

1-5747150-4

TE Internal Number: 1-5747150-4

Always EU RoHS/ELV Compliant

Connector Style Receptacle

Centerline (in) .108

Number of Positions 9

Number of Rows 2

Shell Size 1

Product Drawings

RECEPTACLE ASSEMBLY, SIZE 1, 9 POSITION FRONT METAL SHELL, WITH OR

WITHOUT SCREWLOCKS OR INSERTS,

PDF English

CAD Files

Customer View Model

2D_DXF.ZIP English

Customer View Model

3D_IGS.ZIP English

Customer View Model

3D_STP.ZIP English

3D PDF

PDF **English**

Catalog Pages/Data Sheets

AMPLIMITE Subminiature D Connectors - Straight Posted Connectors

PDF **English**

Product Specifications

Product Specification AMPLIMITE HD-20 PCB Mounted Connector

PDF **English**

AMPLIMITE HD-20 Straight Solder Contact Tine, Front Metal Shell, PC Board And Application Specification

Panel Mount Connectors

Qualification Test Report Connector, AMPLIMITE HD-20, Printed Circuit Board Mounted

PDF **English**

Product Environmental Compliance

TE Material Declaration MD_1-5747150-4_0616201413_dmtec

PDF **English**


Please review product documents or contact us for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Connector Style	Receptacle
	Shell Size	1
	Profile	Standard
	PCB Mounting Orientation	Vertical
	Grounding Straps	Without
	Shell Type	Front Metal Shell
	Grounding Indents	Without
	Applies To	Printed Circuit Board
	Sealed	No
	Product Type	Connector
Configuration Features	Number of Positions	9
	Number of Rows	2
	Preloaded	Yes
Body Features	Plastic	No
	Female Screwlock Material	Zinc
	Color Code	None
	Shell Plating Material	Tin
	Insert Material	Brass
	Shell Material	Carbon Steel
	Post Size	.66 mm [.026 in]
Contact Features	Contact Shape	Round
	Solder Tail Contact Plating Material	Tin over Nickel
	Contact Base Material	Phosphor Bronze
	Contact Mating Area Plating Thickness (µin)	30
	Contact Mating Area Plating Material	Gold
Termination Features	Termination Post Length	3.18 mm [.125 in]
	Grounding Clips	Without

Mechanical Attachment PCB Mounting Style Through Hole

Product Compliance	Statement of Compliance	
Other	Comment	All receptacles are preloaded with size 20 DF posted socket contacts
	Packaging Quantity	17
Packaging Features	Packaging Method	Tube
Industry Standards	UL Flammability Rating	UL 94V-0
Dimensions	PCB Thickness (Recommended)	1.57 – 2.36 mm [.062 – .093 in]
	Housing Material	Polyester
	Housing Color	Black
Housing Features	Centerline (in)	.108
	Mounting Hole Diameter	3.05 mm [.12 in]
	Panel Mount Retention	Without
	Mating Connector Lock Type	Female Screwlocks, Fixed
	Mating Connector Lock	With
	PCB Mount Retention Type	Mounting Holes
	PCB Mount Retention	With
Trochamour / Washinson	r ob mounting style	491

CUSTOMERS ALSO BOUGHT



VIEW ALL PRODUCT COMPLIANCE



Relation Type

RELATIONSHIP

Mating Products

Used to identify Mating Parts

See All Mating Products



PRODUCT - MATING PRODUCTS

Connectors - IDC D-Sub Connectors AMPLIMITE | HDE (IDC) Insulation

09 SHLDG ENCL PLUG, LEAD FREE - 1-747944-5 TE INTERNAL NUMBER: 1-747944-5

E INTERNAL NOMBER. 1-7-77744

✓ Active

Always EU RoHS/ELV Compliant

Connector Style Plug

Shielded Yes

Number of Positions 9

Number of Rows 2

Preloaded Yes

RELATIONSHIP

Mating Products

Used to identify Mating Parts

See All Mating Products



PRODUCT - MATING PRODUCTS

Connectors - IDC D-Sub Connectors AMPLIMITE I HDF for Flat Ribbon Cable

09 POS HDF PLUG, MS, LEAD FREE - 1658613-4

TE INTERNAL NUMBER: 1658613-4

✓ Active

Always EU RoHS/ELV Compliant

Connector Style Plug

Number of Positions 9

Number of Rows 2

Preloaded **Yes**

Contact Size 20

RELATIONSHIP

Mating Products

Used to identify Mating Parts

See All Mating Products



PRODUCT - MATING PRODUCTS

Connectors - IDC D-Sub Connectors AMPLIMITE | HDF for Flat Ribbon Cable

9 POS HDF PLUG, MS - 5746862-4

TE INTERNAL NUMBER: 5746862-4

✓ Active

Always EU RoHS/ELV Compliant

Connector Style **Plug**

Number of Positions 9

Number of Rows 2

Preloaded **Yes**

Contact Size 20

