

RECTANGULAR POWER CONNECTORS



PRODUCT DRAWING

Ŧ

English

J 3D PDF

TE CONNECTIVITY (TE) 14P MTA156 HDR ASSY RN STR F/L MTA | MTA156

1-640388-4 TE Internal Number: 1-640388-4

Always EU RoHS/ELV Compliant

Product Type Header
Housing Type Plug
Connector System Wire-to-Board
Applies To Printed Circuit Board
Contact Current Rating (A) 7

Product Drawings	MTA156 HEADER ASSEMBLY, FRICTION LOCK, STRAIGHT .045 ROUND POST, TIN PLATED PDF English
CAD Files	Customer View Model 3D_STP.ZIP English
	Customer View Model 2D_DXF.ZIP English
	3D PDF PDF 3D
	Customer View Model 3D_IGS.ZIP English
Catalog Pages/Data Sheets	MTA, CST-100 II, SL-156 And AMP Economy Power (EP) Connectors PDF English
Product Environmental Compliance	
TE Material Declaration	14P MTA156 HDR ASSY RN STR F/L PDF English
	MD_1-640388-4_03132014451_dmtec PDF English

Please review product documents or **contact us** for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

У 🖬 f v

Product Type Features Configuration Features	Product Type Housing Type Contact Type Header Type Number of Positions Centerline PCB Mounting Orientation Number of Rows Contact Layout	Header Plug Pin Unshrouded 14 3.96 mm [.156 in] Vertical 1 Inline
Electrical Characteristics	Contact Current Rating (A) Operating Voltage (VAC)	7 600
Contact Features	Contact Retention Contact Termination Area Plating Material Contact Mating Area Plating Material Contact Mating Area Plating Thickness Contact Base Material Underplate Material Thickness Contact Termination Area Plating Thickness Underplate Material	Without Tin Tin 2.54 µm [100 µin] Copper Alloy 1.27 µm [50 µin] 2.54 µm [100 µin] Nickel
Termination Features	Termination Method to Wire/Cable Termination Method to PC Board Termination Post/Tail Length	Solder Through Hole - Solder 3.18 mm [.125 in]
Mechanical Attachment	Mating Alignment Mating Retention PCB Mount Retention PCB Mount Alignment Mating Retention Type Panel Mount Retention Strain Relief	Without With Without Friction Lock Without Without
Housing Features	UL Flammability Rating Housing Color	UL 94V-0 Natural

	Housing Material	Polyester
Dimensions	Mating Post Length	10.16 mm [.4 in]
	Height	10.79 mm [.425 in]
	PCB Thickness (Recommended)	1.6 mm [.063 in]
	Length	55.47 mm [2.184 in]
Usage Conditions	Sealed Condition	Not Sealed
Operation/Application	Connector System	Wire-to-Board
	Applies To	Printed Circuit Board
	Operating Temperature	-55 – 105 °C [-67 – 221 °F]
Industry Standards	CSA Rating	Certified
	Agency/Standard Number	E28476
	UL Rating	Recognized
	CSA File Number	LR7189
	Agency/Standard	CSA, UL
Packaging Features	Packaging Method	Package
	Packaging Quantity	500
Other	Backwall/Post Interruptions	Without
	For Use With	MTA .156 Connector Assembly or SL .156 Connector Assembly
Product Compliance	Statement of Compliance	
	VIEW ALL PRODUCT COMPLIANCE	
Products - 59 Results		View All Compare 0/10
Relation Type 🔻		
RELATIONSHIP		

RELATIONSHIP **Mating Products** Used to identify Mating Parts

See All Mating Products



PRODUCT - MATING PRODUCTS

Connectors - W-T-B Headers & Receptacles MTA I MTA 156 14P MTA 156 CONN ASSY 20AWG LF - 4-640605-4 TE INTERNAL NUMBER: 4-640605-4

Always EU RoHS/ELV Compliant

Centerline 3.96 mm

Number of Positions 14

Number of Rows 1

Contact Mating Area Plating Material **Tin**

Contact Mating Area Plating Material Finish **Matte**

Contact Mating Area Plating Material Finish **Matte**

RELATIONSHIP **Mating Products** Used to identify Mating Parts

See All Mating Products

See All Mating Products



RELATIONSHIP **Mating Products** Used to identify Mating Parts



Mating Retention With