




RECTANGULAR POWER CONNECTORS



Active

PRODUCT DRAWING
English

3D PDF

TE CONNECTIVITY (TE) 02P MR II CAP HSG V0 RED

AMP | CAP , Miniature Rectangular

1-640507-0
TE Internal Number: 1-640507-0

Always EU RoHS/ELV Compliant

Product Type **Housing**

Housing Type **Receptacle**

Connector System **Wire-to-Panel, Wire-to-Wire**

Applies To **Wire/Cable**

Number of Positions **2**

Product Drawings

[HOUSING, CAP MR II 2 POSITION](#)

PDF
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

[3D PDF](#)

PDF
English

Catalog Pages/Data Sheets

[SOFT_SHELL_PIN_AND_SOCKET_CONNECTORS_CATALOG](#)

PDF
English

Product Specifications

Product Specification

[Connector, Miniature Rectangular \(MR\)](#)

PDF
English

Application Specification

[Miniature Rectangular Contacts And Housings](#)

PDF
English

Qualification Test Report

[Connector, Miniature Rectangular \(MR\)](#)

PDF
English

[Connector, Miniature Rectangular \(MR\)](#)

TIF
English

Product Environmental Compliance

TE Material Declaration

[MD_1-640507-0_050320131024_dmtec](#)

PDF

Instruction Sheets

Instruction Sheet (U.S.)

AMP* MINIATURE RECTANGULAR II (MRII) CONNECTORS

PDF
English

AMP* MINIATURE RECTANGULAR II (MRII) CONNECTORS

TIF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Product Type	Housing
	Housing Type	Receptacle
	Contact Type	Pin
Configuration Features	Number of Positions	2
	Centerline	4.2 mm [.165 in]
	Number of Signal Positions	2
	Number of Rows	1
Electrical Characteristics	Operating Voltage (VAC)	250
Mechanical Attachment	Panel Mount Retention	Without
Housing Features	UL Flammability Rating	UL 94V-0
	Housing Color	Brick Red
Dimensions	Length	26.92 mm [1.06 in]
	Height	7.37 mm [.29 in]
	Accepts Wire Insulation Diameter Range	2.92 mm [.115 in]
	Width	12.95 mm [.51 in]
Usage Conditions	Sealed Condition	Not Sealed
Operation/Application	Connector System	Wire-to-Panel, Wire-to-Wire
	Applies To	Wire/Cable
	Operating Temperature	-55 – 105 °C [-67 – 221 °F]





Industry Standards	UL Rating	Recognized
	CSA File Number	LR7189
	Agency/Standard	CSA, UL
	Agency/Standard Number	E28476
Packaging Features	Packaging Method	Box
	Packaging Quantity	200

Product Compliance

[Statement of Compliance PDF](#)

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

<p>RECTANGULAR POWER CONNECTORS</p>  <p>02P MR II PLUG HSG V0 RED 1-640517-0</p> <p>Save to List Find Similar Products</p>	<p>RECTANGULAR POWER CONNECTORS</p>  <p>04P MR II CAP HSG V0 RED 1-640509-0</p> <p>Save to List Find Similar Products</p>	<p>POWER CONTACTS</p>  <p>III+ PIN, 18-14, 30AU/FL, STRIP 66597-2</p> <p>Save to List Find Similar Products</p>	<p>RECTANGULAR POWER CONNECTORS</p>  <p>PLUG, 2 CIRCUIT, UNIVERSAL MATE-N-LOK 1-1703061-2</p> <p>Save to List Find Similar Products</p>
---	---	---	---

Products - 1 Results

[View All](#)

[Compare 0/10](#)

Relation Type ▼

RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

<p>PRODUCT - MATING PRODUCTS</p> 	<p>Connectors - Rectangular Power Connectors AMPI HS, Miniature Rectangular</p> <p>02P MR II PLUG HSG V0 RED - 1-640517-0</p> <p>TE INTERNAL NUMBER: 1-640517-0 ALIAS ID: 11998</p> <p>✓ Active</p>	<p>Always EU RoHS/ELV Compliant</p> <p>Product Type Housing</p> <p>Housing Type Plug</p> <p>Connector System Wire-to-Board, Wire-to-Panel, Wire-to-Wire</p> <p>Applies To Wire/Cable</p> <p>Number of Positions 2</p>	<input checked="" type="checkbox"/>
--	--	--	-------------------------------------

