


RECTANGULAR POWER CONNECTORS





✓ Active

<u>+</u>

PRODUCT DRAWING



3D PDF

TE CONNECTIVITY (TE)
03P MR II PLUG HSG V0 RED

AMP | HS , Miniature Rectangular

1-640518-0

TE Internal Number: 1-640518-0

Always EU RoHS/ELV Compliant

Product Type **Housing**Housing Type **Plug**

Connector System Wire-to-Board, Wire-to-Panel, Wire-to-Wire

Applies To Wire/Cable

Number of Positions 3

Product Drawings HOUSING, PLUG MRII 3 POSITION

PDF (TIFF AVAILABLE)

English

HOUSING, PLUG MRII 3 POSITION

PDF (TIFF AVAILABLE)

English

CAD Files Customer View Model

2D_DXF.ZIP English

Customer View Model

3D_IGS.ZIP **English**

Customer View Model

3D_STP.ZIP **English**

3D PDF PDF English

Catalog Pages/Data Sheets SOFT_SHELL_PIN_AND_SOCKET_CONNECTORS_CATALOG

PDF **English**

Product Specifications

Product Specification Connector, Minature Rectangular (MR)

PDF **English**

Application Specification Miniature Rectangular Contacts And Housings

English

Qualification Test Report Connector, Miniature Rectangular (MR)

English

Connector, Miniature Rectangular (MR)

TIF English

Instruction Sheets

Instruction Sheet (U.S.)

AMP* MINIATURE RECTANGULAR II (MRII) CONNECTORS

PDF **English**

AMP* MINIATURE RECTANGULAR II (MRII) CONNECTORS

TIF English


Please review product documents or contact us for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.


Product Type Features	Product Type	Housing
	Housing Type	Plug
	Contact Type	Socket
Configuration Features	Number of Positions	3
	Centerline	4.2 mm [.165 in]
	Number of Signal Positions	1
	Number of Rows	1
Electrical Characteristics	Operating Voltage (VAC)	250
Mechanical Attachment	Panel Mount Retention	Without
Housing Features	UL Flammability Rating	UL 94V-0
	Housing Color	Brick Red
Dimensions	Length	21.34 mm [.84 in]
	Height	12.95 mm [.51 in]
	Accepts Wire Insulation Diameter Range	2.92 mm [.115 in]
	Width	12.95 mm [.51 in]
Usage Conditions	Sealed Condition	Not Sealed
Operation/Application	Connector System	Wire-to-Board, Wire-to-Panel, Wire-to-Wire
	Applies To	Wire/Cable
	Operating Temperature	-55 – 105 °C [-67 – 221 °F]
Industry Standards	UL Rating	Recognized
	CSA File Number	LR7189

	Agency/Standard	CSA, UL
	Agency/Standard Number	E28476
Packaging Features	Packaging Method	Вох
	Packaging Quantity	2000
Product Compliance	Statement of Compliance	

VIEW ALL PRODUCT COMPLIANCE

CUSTOMERS ALSO BOUGHT





RELATIONSHIP

Mating Products

Used to identify Mating Parts

See All Mating Products



PRODUCT - MATING PRODUCTS

Connectors - Rectangular Power Connectors AMP I HD.25, Miniature Rectangular

AMP1 HD.25, Miniature Rectangular

03P MR HDR ASSY VO

RED LF - 2-640498-4 TE INTERNAL NUMBER: 2-640498-4

✓ Active

Always EU RoHS/ELV Compliant



RELATIONSHIP

Mating Products

Used to identify Mating Parts

See All Mating Products



PRODUCT - MATING PRODUCTS

Connectors - Rectangular Power Connectors AMP I HD.25, Miniature Rectangular

03P MR HDR ASSY V0 RED - 640498-1

TE INTERNAL NUMBER: 640498-1

✓ Active



Always EU RoHS/ELV Compliant