

RECTANGULAR POWER CONNECTORS



Product Drawings	HOUSING, PLUG MRII 12 POSITION PDF (TIFF AVAILABLE) English HOUSING, PLUG MRII 12 POSITION PDF (TIFF AVAILABLE) English
CAD Files	Customer View Model 2D_DXF.ZIP English
	Customer View Model
	3D_STP.ZIP English
	Customer View Model
	3D_IGS.ZIP English
	3D PDF
	PDF English
Catalog Pages/Data Sheets	SOFT_SHELL_PIN_AND_SOCKET_CONNECTORS_CATALOG PDF English
Product Specifications	
Product Specification	Connector, Minature Rectangular (MR) PDF English
Application Specification	Miniature Rectangular Contacts And Housings PDF English
Qualification Test Report	Connector, Miniature Rectangular (MR)

Connector, Miniature Rectangular (MR) TIF **English**

PDF **English**

Ƴ ⊡ f v

Product Environmental Compliance

 TE Material Declaration
 12P MR II PLUG HSG VO RED

 PDF
 English

 Instruction Sheets
 AMP* MINIATURE RECTANGULAR II (MRII) CONNECTORS

 PDF
 English

 AMP* MINIATURE RECTANGULAR II (MRII) CONNECTORS

 PDF
 English

 AMP* MINIATURE RECTANGULAR II (MRII) CONNECTORS

 TIF
 English

Please review product documents or **contact us** for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Product Type	Housing
	Housing Type	Plug
	Contact Type	Socket
Configuration Features	Number of Positions	12
	Centerline	4.19 mm [.165 in]
	Number of Signal Positions	12
	Number of Rows	4
	Row-to-Row Spacing	4.19 mm [.165 in]
Electrical Characteristics	Operating Voltage (VAC)	250
Mechanical Attachment	Panel Mount Retention	Without
Housing Features	UL Flammability Rating	UL 94V-0
	Housing Color	Brick Red
Dimensions	Length	21.34 mm [.84 in]
	Height	12.95 mm [.51 in]
	Accepts Wire Insulation Diameter Range	2.92 mm [.115 in]
	Width	25.53 mm [1.17 in]
Usage Conditions	Sealed Condition	Not Sealed
Operation/Application	Connector System	Wire-to-Board, Wire-to-Panel, Wire-to-Wire
	Applies To	Wire/Cable

whhiles in **** Cable Operating Temperature -55 – 105 °C [-67 – 221 °F] Industry Standards UL Rating Recognized CSA File Number LR7189 Agency/Standard CSA, UL Agency/Standard Number E28476 Packaging Features Packaging Method Box Packaging Quantity 800

Product Compliance

Statement of Compliance PDF

VIEW ALL PRODUCT COMPLIANCE

CUSTOMERS ALSO BOUGHT

POWER CONTACTS	POWER CONTACTS	POWER CONTACTS	RECTANGULAR BOOTS & STRAIN RELIEF	
MR RECEPTACLE AU PHBZ 794000-2	MR RECEPTACLE PTPPHBZ 794000-1	MR RECPT PTPPHBZ LP 26- 24	12P STR/REL HSG HNGE V0	>
		794001-1	350374-1	
€ Save to List	🔁 Save to List	🔁 Save to List	Save to List	1
Find Similar Products	Find Similar Products	Find Similar Products	••• Find Similar Products	1
•				Þ

Pro	ducts - 5 Results		View All	Compare 0/10	
	Relation Type	•			
Ma	ATIONSHIP ting Products d to identify Mating Parts			See All Mating Proc	ducts
	_	PRODUCT - MATING PRODUCTS			~
		Connectors - Rectangular Power Connectors Alway: AMP112P, Miniature Rectangular 12P MR HDR ASSY VO RED - 640502-1 TE INTERNAL NUMBER: 640502-1	s EU RoHS/ELV Compliar	t	

RELATIONSHIP **Mating Products** Used to identify Mating Parts





PRODUCT - MATING PRODUCTS

Connectors - Rectangular Power Connectors AMPI 12P, Miniature Rectangular 12P MR II CAP HSG VO RED - 1-640512-0 TE INTERNAL NUMBER: 1-640512-0

✓ Active

Always EU RoHS/ELV Compliant

Product Type **Housing**

Housing Type **Receptacle**

Connector System Wire-to-Panel,

Always EU RoHS/ELV Compliant

Applies To Wire/Cable

Wire-to-Wire

Number of Positions 12

RELATIONSHIP **Mating Products** Used to identify Mating Parts

See All Mating Products

.



PRODUCT - MATING PRODUCTS

Connectors - Rectangular Power Connectors AMPI 12P, Miniature Rectangular 12P MR HDR ASSY VO

RED - 640502-3 TE INTERNAL NUMBER: 640502-3

✓ Active