

## **RECTANGULAR POWER CONNECTORS**





✓ Active



PRODUCT DRAWING



3D PDF

# TE CONNECTIVITY (TE) 20P MR II PLUG HSG V0 RED

AMP | HS , Miniature Rectangular

1-640524-0

TE Internal Number: 1-640524-0

Always EU RoHS/ELV Compliant

Product Type **Housing**Housing Type **Plug** 

Connector System Wire-to-Board, Wire-to-Panel, Wire-to-Wire

Applies To Wire/Cable

Number of Positions 20

Product Drawings HOUSING, PLUG MRII 20 POSITION

PDF (TIFF AVAILABLE)

English

HOUSING, PLUG MRII 20 POSITION

PDF (TIFF AVAILABLE)

English

CAD Files Customer View Model

2D\_DXF.ZIP English

**Customer View Model** 

3D\_IGS.ZIP **English** 

**Customer View Model** 

3D\_STP.ZIP English

3D PDF PDF English

Catalog Pages/Data Sheets SOFT\_SHELL\_PIN\_AND\_SOCKET\_CONNECTORS\_CATALOG

PDF **English** 

**Product Specifications** 

Product Specification Connector, Minature Rectangular (MR)

PDF **English** 

Application Specification Miniature Rectangular Contacts And Housings

English

Qualification Test Report Connector, Miniature Rectangular (MR)

PDF **English** 

Connector, Miniature Rectangular (MR)

TIF English

#### Instruction Sheets

Instruction Sheet (U.S.)

### AMP\* MINIATURE RECTANGULAR II (MRII) CONNECTORS

PDF **English** 

### AMP\* MINIATURE RECTANGULAR II (MRII) CONNECTORS

TIF English

Please review product documents or contact us for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Product Type	Housing
	Housing Type	Plug
	Contact Type	Socket
Configuration Features	Number of Positions	20
Computation relatives		
	Centerline	4.19 mm [ .165 in ]
	Number of Signal Positions	20
	Number of Rows	5
	Row-to-Row Spacing	4.19 mm [ .165 in ]
Electrical Characteristics	Operating Voltage (VAC)	250
Mechanical Attachment	Panel Mount Retention	Without
Housing Features	UL Flammability Rating	UL 94V-0
	Housing Color	Brick Red
Dimensions	Length	21.34 mm [ .84 in ]
	Height	12.95 mm [ .51 in ]
	Accepts Wire Insulation Diameter Range	2.92 mm [ .115 in ]
	Width	29.72 mm [ 1.17 in ]
Usage Conditions	Sealed Condition	Not Sealed
Operation/Application	Connector System	Wire-to-Board, Wire-to-Panel, Wire-to-Wire
	Applies To	Wire/Cable

Industry Standards UL Rating Recognized

CSA File Number LR7189

Agency/Standard CSA, UL

Agency/Standard Number E28476


Packaging Features Packaging Method Box


Packaging Quantity 600

Product Compliance Statement of Compliance PDF

VIEW ALL PRODUCT COMPLIANCE

### **CUSTOMERS ALSO BOUGHT**





# **Mating Products**

Used to identify Mating Parts

See All Mating Products

See All Mating Products



PRODUCT - MATING PRODUCTS

Connectors - Rectangular Power Connectors AMP | HD.25, Miniature Rectangular

20P MR HDR ASSY VO RED LF - 2-640504-2

TE INTERNAL NUMBER: 2-640504-2

✓ Active

Always EU RoHS/ELV Compliant



RELATIONSHIP

#### **Mating Products**

Used to identify Mating Parts



PRODUCT - MATING PRODUCTS

Connectors - Rectangular Power Connectors AMP I CAP, Miniature Rectangular

20P MR II CAP HSG V0 RED - 1-640514-0 TE INTERNAL NUMBER: 1-640514-0

✓ Active

Always EU RoHS/ELV Compliant

Product Type **Housing** 

Housing Type **Receptacle** 

Connector System Wire-to-Panel,

Wire-to-Wire

Applies To Wire/Cable

Number of Positions 20

