



# RECTANGULAR POWER CONNECTORS



TE CONNECTIVITY (TE)

## 14P MINI UMNL R/A HDR ASSY SN

MATE-N-LOK | Mini-Universal MATE-N-LOK Connectors

1-770973-0

TE Internal Number: 1-770973-0

Always EU RoHS/ELV Compliant

Product Type **Header**

Housing Type **Plug**

Connector System **Wire-to-Board**

Applies To **Printed Circuit Board**

Contact Current Rating (A) **9.5**

Active

PRODUCT DRAWING  
English

3D PDF

### Product Drawings

HEADER ASSEMBLY, RIGHT ANGLE, WITH SHORT PEG, 14 CIRCUIT, MINI UNIVERSAL MATE-N-LOK(TM)

PDF  
English

### CAD Files

3D PDF

PDF  
English

Customer View Model

2D\_DXF.ZIP  
English

Customer View Model

3D\_IGS.ZIP  
English

Customer View Model

3D\_STP.ZIP  
English

### Catalog Pages/Data Sheets

SOFT\_SHELL\_PIN\_AND\_SOCKET\_CONNECTORS\_CATALOG

PDF  
English

1-1773458-0\_MINI\_UNIVERSAL\_MATE\_N\_LOK\_CONNECTOR\_SYSTEM\_QRG

PDF  
English

### Product Specifications

Application Specification

Mini-Universal MATE-N-LOK Connectors

PDF  
English

### Product Environmental Compliance

TE Material Declaration

MD\_1-770973-0\_02262016825\_dmtec

PDF  
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

---

Product Type Features	Product Type	<b>Header</b>
	Housing Type	<b>Plug</b>
	Contact Type	<b>Pin</b>

---

Configuration Features	Number of Positions	<b>14</b>
	Centerline	<b>4.14 mm [ .163 in ]</b>
	PCB Mounting Orientation	<b>Right Angle</b>
	Number of Rows	<b>2</b>
	Row-to-Row Spacing	<b>4.14 mm [ .163 in ]</b>
	Multiple Contact Types	<b>Without</b>

---

Electrical Characteristics	Contact Current Rating (A)	<b>9.5</b>
	Operating Voltage (VAC)	<b>600</b>
	Operating Voltage (VDC)	<b>600</b>

---

Contact Features	Contact Retention	<b>Without</b>
	Contact Termination Area Plating Material	<b>Tin</b>
	Contact Termination Area Plating Thickness	<b>3.81 <math>\mu</math>m [ 150 <math>\mu</math>in ]</b>

---

Termination Features	Termination Method to Wire/Cable	<b>Solder</b>
	Termination Method to PC Board	<b>Through Hole - Solder</b>
	Termination Post/Tail Length	<b>3.69 mm [ .145 in ]</b>

---

Mechanical Attachment	Mating Alignment	<b>With</b>
	Mating Retention	<b>With</b>
	PCB Mount Retention	<b>With</b>
	PCB Mount Retention Type	<b>Boardlocks</b>
	Mating Alignment Type	<b>Chamfered Edges</b>
	PCB Mount Alignment	<b>Without</b>
	Assembly Integration Feature	<b>Without</b>
	Mating Retention Type	<b>Locking Tab</b>
	Panel Mount Retention	<b>Without</b>
	Strain Relief	<b>Without</b>

---

Housing Features	UL Flammability Rating	<b>UL 94V-0</b>
	Housing Color	<b>White</b>
	Housing Material	<b>Nylon</b>
Dimensions	Width (mm)	<b>12.7</b>
	Height (mm)	<b>11.86</b>
	PCB Thickness (Recommended)	<b>1.57 mm [ .062 in ]</b>
	Length (mm)	<b>30.56</b>
	Insulation Diameter (Max) (mm)	<b>3.2</b>
Usage Conditions	Sealed Condition	<b>Not Sealed</b>
Operation/Application	Connector System	<b>Wire-to-Board</b>
	Applies To	<b>Printed Circuit Board</b>
	Operating Temperature	<b>-55 – 105 °C [ -67 – 221 °F ]</b>
Industry Standards	Glow Wire Rating	<b>Standard Part - Not Glow Wire</b>
	VDE Tested	<b>Yes</b>
	CSA Rating	<b>Certified</b>
	Agency/Standard Number	<b>E28476</b>
	UL Rating	<b>Recognized</b>
	CSA File Number	<b>LR7189</b>
	Agency/Standard	<b>CSA, UL</b>
Packaging Features	Packaging Method	<b>Bag</b>
	Packaging Quantity	<b>200</b>
Other	For Use With	<b>Plug Housing</b>
Product Compliance	<a href="#">Statement of Compliance</a> PDF <a href="#">VIEW ALL PRODUCT COMPLIANCE</a>	

Products - 2 Results

[View All](#)

Compare 0/10



Relation Type ▼

RELATIONSHIP

## Mating Products

Used to identify Mating Parts

[See All Mating Products](#)



PRODUCT - MATING PRODUCTS

Connectors - Rectangular Power Connectors  
MATE-N-LOK I Mini-Universal MATE-N-LOK 2

### 14P MINI UMNL2 PLUG HSG UL94V0 - 794202-1

TE INTERNAL NUMBER: 794202-1  
ALIAS ID: 0-0794202-1

✓ Active

Always EU RoHS/ELV Compliant

Product Type **Housing**

Housing Type **Plug**

Connector System **Wire-to-Wire**

Applies To **Wire/Cable**

Number of Positions **14**



RELATIONSHIP

## Mating Products

Used to identify Mating Parts

[See All Mating Products](#)



PRODUCT - MATING PRODUCTS

Connectors - Rectangular Power Connectors  
MATE-N-LOK I Mini-Universal MATE-N-LOK

### 14P MINI UMNL PLUG HSG - 770582-1

TE INTERNAL NUMBER: 770582-1

✓ Active

Always EU RoHS/ELV Compliant

Product Type **Housing**

Housing Type **Plug**

Connector System **Wire-to-Wire**

Applies To **Wire/Cable**

Number of Positions **14**

