

✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

14 POS AMPSEAL VERTICAL HDR

AMP | AMPSEAL

1-776262-1

TE Internal Number: 1-776262-1

Always EU RoHS/ELV Compliant

Pin Diameter **1.3 mm [.051 in]**

Pitch **4 mm [.157 in]**

Number of Circuits **14**

Sealed **Yes**

Mounting Orientation **Vertical/180°**

Product Drawings

[ASSEMBLY, HEADER, 14 POSITION, VERTICAL, AMPSEAL WITH FLANGE SEAL](#)

PDF
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[3D PDF](#)

PDF
3D

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Product Specifications

Application Specification

[AMPSEAL Automotive Plug Connector And Header Assembly](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Sealed	Yes
Hybrid Header	No
Shielded	No

Configuration Features

Number of Circuits	14
--------------------	-----------

	Number of Rows	3
	Number of Sections	1
	Number of Signal Positions	14
Electrical Characteristics	Nominal Voltage Architecture (V)	12, 24, 42, 48, 240
	Voltage Rating (Max) (VAC)	250
	Operating Voltage (VAC)	250
Body Features	Color	Black
Contact Features	Pin Diameter	1.3 mm [.051 in]
	Circuit Application	Power, Signal
	Interface Plating	Gold (Au)
Termination Features	Termination Method	Through Hole - Solder
Mechanical Attachment	Mounting Orientation	Vertical/180°
	PCB Mount Retention Type	Solder Tails
	PCB Mount Retention	Without
	Panel Mount Retention	Without
	Mounting Holes	With
	PCB Mount Alignment	With
	Locking Interface	With
Housing Features	Pitch	4 mm [.157 in]
Dimensions	Profile Height from PCB	34.3 mm [1.35 in]
	Width	32.1 mm [1.264 in]
	PCB Thickness (Recommended)	1.57 mm [.062 in]
	Length	48.8 mm [1.9212 in]
Usage Conditions	Operating Temperature (Max) (°C)	65, 70, 75, 80, 85, 90, 100, 105
	Operating Temperature (Max) (°F)	149, 158, 167, 176, 185, 194, 212, 221
	Operating Temperature Range	-40 – 105 °C [-40 – 221 °F]
Industry Standards	Degree of Protection	IP6K9K

Packaging Features

Packaging Quantity

1

Product Compliance

[Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

Products - 1 Results

[View All](#)

Compare 0/10

Relation Type


RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

PRODUCT - MATING PRODUCTS



Connectors - Automotive, Truck, Bus, & Off-Road Housings
AMP | AMPSEAL

14P AMPSEAL PLUG ASSEMBLY - 776273-1

TE INTERNAL NUMBER: 776273-1

Active

Always EU RoHS/ELV Compliant

Connector Style **Housing for female terminals**

Mating Pin Diameter **1.3 mm**

Number of Positions **14**

Pitch **4 mm**

Sealed **Yes**