



RECTANGULAR POWER CONNECTORS



TE CONNECTIVITY (TE)

12P MINI UMNL HDR ASSY AUBR LF

MATE-N-LOK | Mini-Universal MATE-N-LOK

1-794040-1

TE Internal Number: 1-794040-1

Always EU RoHS/ELV Compliant

Product Type **Header**

Housing Type **Plug**

Connector System **Wire-to-Board**

Applies To **Printed Circuit Board**

Contact Current Rating (A) **9.5**

Active

PRODUCT DRAWING
English

3D PDF

Product Drawings

[HEADER ASSEMBLY, CLOSED BOTTOM, 12 CIRCUIT, MINI-UNIVERSAL MATE-N-LOK](#)

PDF
English

CAD Files

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

[Customer View Model](#)

2D_DXF.ZIP
English

[3D PDF](#)

PDF
English

Catalog Pages/Data Sheets

[SOFT_SHELL_PIN_AND_SOCKET_CONNECTORS_CATALOG](#)

PDF
English

[1-1773458-0_MINI_UNIVERSAL_MATE_N_LOK_CONNECTOR_SYSTEM_QRG](#)

PDF
English

Product Specifications

Application Specification

[Mini-Universal MATE-N-LOK Connectors](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_1-794040-1_02262016826_dmtec](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Product Type	Header
	Housing Type	Plug
	Contact Type	Pin
	Header Type	Shrouded

Configuration Features	Number of Positions	12
	Centerline	4.14 mm [.163 in]
	PCB Mounting Orientation	Vertical
	Number of Rows	3
	Row-to-Row Spacing	4.14 mm [.163 in]
	Multiple Contact Types	Without
	Contact Layout	Matrix

Electrical Characteristics	Contact Current Rating (A)	9.5
	Operating Voltage (VAC)	600
	Operating Voltage (VDC)	600





Contact Features	Contact Retention	Without
	Contact Termination Area Plating Material	Tin
	Contact Mating Area Plating Material	Gold
	Contact Termination Area Plating Thickness	3.81 µm [150 µin]

Termination Features	Wire/Cable Size (AWG)	30 – 16
	Wire/Cable Size (mm ²)	.05 – 1.2
	Termination Method to Wire/Cable	Solder
	Termination Method to PC Board	Through Hole - Solder
	Termination Post/Tail Length (mm)	.76, 4.45
	Termination Post/Tail Length (in)	.175

Mechanical Attachment	Mating Alignment	With
	Mating Retention	With
	PCB Mount Retention	With
	PCB Mount Retention Type	Boardlocks
	Mating Alignment Type	Chamfered Edges

	PCB Mount Alignment	Without
	Assembly Integration Feature	Without
	Mating Retention Type	Locking Tab
	Panel Mount Retention	Without
	Strain Relief	Without
Housing Features	UL Flammability Rating	UL 94V-0
	Housing Color	White
	Housing Material	Nylon
Dimensions	Width (mm)	13.97
	Height (mm)	13.49
	PCB Thickness (Recommended)	1.57 mm [.062 in]
	Length (mm)	18.11
Usage Conditions	Sealed Condition	Not Sealed
Operation/Application	Connector System	Wire-to-Board
	Applies To	Printed Circuit Board
	Operating Temperature	-55 – 105 °C [-67 – 221 °F]
Identification Marking	Circuit Identification Feature	Without
Industry Standards	Glow Wire Rating	Standard Part - Not Glow Wire
	VDE Tested	No
	CSA Rating	Certified
	Agency/Standard Number	E28476
	UL Rating	Recognized
	CSA File Number	LR7189
	Agency/Standard	CSA, UL
Packaging Features	Packaging Method	Bag
	Packaging Quantity	200
Other	For Use With	Plug Housing

CUSTOMERS ALSO BOUGHT

MOTOR TERMINAL HOUSINGS	SMC CONNECTORS	RECTANGULAR POWER CONNECTORS	TERMINAL BLOCK HEADERS & RECEPTACLES
 <p>FLG-FAST INSUL POD LP/R 480296 1-480306-1</p> <p>Save to List Find Similar Products</p>	 <p>SMC Str PCB Skt 50Ohm Gold Plt 1-1337485-0</p> <p>Save to List Find Similar Products</p>	 <p>02P MTA156 HDR ASSY FL/ST LF 3-641120-2</p> <p>Save to List Find Similar Products</p>	 <p>3 POS TERMI-BLOK VERT HDR 7.62 796980-3</p> <p>Save to List Find Similar Products</p>

Products - 2 Results

[View All](#)

[Compare 0/10](#)


Relation Type ▼

RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)


PRODUCT - MATING PRODUCTS		
 <p>Connectors - Rectangular Power Connectors MATE-N-LOK I Mini-Universal MATE-N-LOK 2</p> <p>12P MINI UMNL2 PLUG HSG MATRIX - 794200-1 TE INTERNAL NUMBER: 794200-1</p> <p>✓ Active</p>	<p>Always EU RoHS/ELV Compliant</p> <p>Product Type Housing</p> <p>Housing Type Plug</p> <p>Connector System Wire-to-Wire</p> <p>Applies To Wire/Cable</p> <p>Number of Positions 12</p>	<input checked="" type="checkbox"/>

RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

PRODUCT - MATING PRODUCTS		
 <p>Connectors - Rectangular Power Connectors MATE-N-LOK I Mini-Universal MATE-N-LOK</p> <p>12 CIR UNIV M-N-L PLUG - 172170-1 TE INTERNAL NUMBER: 172170-1</p> <p>✓ Active</p>	<p>Always EU RoHS/ELV Compliant</p> <p>Product Type Housing</p> <p>Housing Type Plug</p> <p>Connector System Wire-to-Wire</p> <p>Applies To Wire/Cable</p>	<input checked="" type="checkbox"/>

