



CONNECTORS

HOUSINGS



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

26 MODIV HSG COMP DR .100 POL

AMPMODU | AMPMODU IV/V

102387-6

TE Internal Number: 102387-6

Alias ID: 010-1079-00

Always EU RoHS/ELV Compliant

Centerline **2.54 mm [.1 in]**

Number of Positions **26**

Number of Rows **2**

Row-to-Row Spacing **2.54 mm [.1 in]**



Product Drawings

HOUSING, CRIMP SNAP-IN, SHORT ENTRY, MOD IV

PDF
English

CAD Files

Customer View Model

2D_DXF.ZIP
English

3D PDF

PDF
3D

Customer View Model

3D_IGS.ZIP
English

Customer View Model

3D_STP.ZIP
English

Catalog Pages/Data Sheets

AMPMODU_INTERCONNECTION_SYSTEM_SECTION5_CONT

PDF
English

Product Specifications

Product Environmental Compliance

TE Material Declaration

[MD_102387-6_11042015917_dmtec](#)
 PDF
 English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Row-to-Row Spacing	2.54 mm [.1 in]
	Glow Wire Rating	Standard Part - Not Glow Wire
	Connector Type	Housing
	Applies To	Wire/Cable
	Connector Style	Receptacle
	Strain Relief	Without
	Product Type	Connector

Configuration Features	Number of Positions	26
	Number of Rows	2
	Stamped	No

Electrical Characteristics	Dielectric Withstanding Voltage	750 V
	Operating Voltage	250 VAC
	Termination Resistance	12 mΩ
	Insulation Resistance (MΩ)	5000

Contact Features	Contact Type	Socket
	Contact Base Material	Beryllium Copper
	Contact Current Rating (A)	3

Termination Features	Termination Method to Wire/Cable	Crimp
----------------------	----------------------------------	--------------

Mechanical Attachment	Mating Connector Lock	Without
	Mating Alignment	With
	Mating Alignment Type	Center

Housing Features	Centerline	2.54 mm [.1 in]
------------------	------------	--------------------------

Housing Features	Centerline	2.95 mm [.118]
	Housing Configuration	Both Ends Closed
	Housing Color	Black
	Housing Material	Thermoplastic
Dimensions	Height	7.23 mm [.285 in]
	Length	37.59 mm [1.48 in]
Usage Conditions	Operating Temperature Range (°C)	-65 – 105
	Flame Retardant	Yes
Operation/Application	For Use With	Header
Industry Standards	Approved Standards	CSA LR7189, UL E28476
	UL Flammability Rating	UL 94V-0
Packaging Features	Packaging Quantity	1
	Packaging Method	Package
Other	Comment	Contact Extraction/Lance Reset Tool No. 843996-3., No marking on this part number., When using this housing with AMP-LATCH Universal Headers, P/N 1825851-1 (Qty 2) must be purchased separately.

Product Compliance

[Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

