

MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES





🛃 3D PDF

TE CONNECTIVITY (TE) 06 MODII HDR SRRA SHRD .100CL AMPMODU | AMPMODU Headers Ƴ ⊡ f v

103361-4 TE Internal Number: 103361-4 Alias ID: 1242309

Not EU RoHS or ELV Compliant Find Compliant Alternatives Applies To Printed Circuit Board Connector Style Plug Centerline 2.54 mm [.1 in] Number of Positions 6 Header Type Shrouded

Product Drawings	HEADER ASSEMBLY, MOD II, SINGLE ROW .100 CL, RIGHT ANGLE PDF English
CAD Files	Customer View Model 2D_DXF.ZIP English
	3D PDF PDF 3D
	Customer View Model 3D_IGS.ZIP English
	Customer View Model 3D_STP.ZIP English

Product Environmental Compliance

TE Material Declaration

MD_103361-4_062920142318_dmtec

English

Please review product documents or **contact us** for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Applies To

Connector Style

PCB Mounting Orientation

Connector Type

Printed Circuit Board

Plug

Right Angle

Header

	Row-to-Row Spacing	2.54 mm [.1 in]
	Stabilizers	Without
	Strain Relief	Without
	Board Standoff	With
	Profile	Standard
	Product Type	Connector
	Gasket	Without
Configuration Features	Number of Positions	6
	Number of Rows	1
	Keyed	No
	Selectively Loaded	No
Electrical Characteristics	Dielectric Withstanding Voltage	750 Vrms
Body Features	Header Type	Shrouded
	Post Size	.64 mm [.025 in]
Contact Features	Contact Protection	With
	Contact Shape	Square
	Contact Type	Pin
	Contact Base Material	Phosphor Bronze
	Contact Mating Area Plating Thickness (µin)	30
	Solder Tail Contact Plating Material	Tin-Lead over Nickel
	Contact Mating Area Plating Material	Gold
	Contact Protection Type	Shrouded
	Contact Current Rating (A)	3
Termination Features	Termination Post Length	2.79 mm [.11 in]
	Termination End Plating Thickness (µin)	100 – 200
	Termination End Plating Material	Tin-Lead Over Nickel
	Termination Method to PC Board	Through Hole
Mechanical Attachment	PCB Mounting Style	Through Hole
	PCB Mount Retention	Without
	Panel Mount Retention	Without

	Mating Alignment	With
	Mating Connector Lock	Without
	Mating Alignment Type	Polarization
Housing Features	Centerline	2.54 mm [.1 in]
	Housing Color	Black
	Housing Material	Thermoplastic
	Housing Style	4-Sided
Dimensions	Shrouded End Dimension	1.778 mm [.07 in]
	PCB Thickness (Recommended)	1.397 mm [.055 in]
	Mating Post Length	6.1 mm [.24 in]
Usage Conditions	Operating Temperature Range (°C)	-65 – 105
	High Temperature Housing	Νο
Operation/Application	High Speed Serial Data Connector	Νο
Industry Standards	UL Flammability Rating	UL 94V-0
	Approved Standards	CSA LR7189, UL E28476
Packaging Features	Packaging Quantity	29
	Packaging Method	Tube
Product Compliance	Statement of Compliance	

VIEW ALL PRODUCT COMPLIANCE

CUSTOMERS ALSO BOUGHT



