

✓ Active

[↓](#) **PRODUCT DRAWING**
English

[↓](#) **3D PDF**

TE CONNECTIVITY (TE)

04 MTE SHRD PIN HSG SR LATCH

[AMPMODU](#) | [AMPMODU MTE](#)

103653-3

TE Internal Number: 103653-3

[Always EU RoHS/ELV Compliant](#)

Centerline **2.54 mm [.1 in]**

Number of Positions **4**

Number of Rows **1**

Row-to-Row Spacing **2.54 mm [.1 in]**

Product Drawings

[PIN HOUSING, AMPMODU MTE, SINGLE ROW, .100 CL POLARIZED WITH LATCH](#)

PDF
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

[3D PDF](#)

PDF
English

Catalog Pages/Data Sheets

[AMPMODU_INTERCONNECTION_SYSTEM_SECTION5_CONT](#)

PDF
English

[AMP MODU MTE Section Of Catalog 1307819](#)

PDF
English

[AMPMODU_MTE_INTERCONNECT_SYSTEM_QRG_4-1773458-0](#)

PDF
English

Product Specifications

Application Specification

[AMPMODU MTE Interconnection System](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_103653-3_04012015316_dmtec](#)

PDF
- - -


Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Row-to-Row Spacing	2.54 mm [.1 in]
	Glow Wire Rating	Standard Part - Not Glow Wire
	Connector Type	Housing
	Connector Style	Plug
	Product Type	Connector
Configuration Features	Number of Positions	4
	Number of Rows	1
Electrical Characteristics	Dielectric Withstanding Voltage	600 VACrms
	Operating Voltage	250 VAC
Contact Features	Contact Type	Pin
	Contact Base Material	Phosphor Bronze
	Contact Current Rating (A)	3
	Contact Layout	Inline
Termination Features	Termination Method to Wire/Cable	Crimp, Insulation Displacement Crimp (IDC)
Mechanical Attachment	Mating Connector Lock	With
	Mating Connector Lock Type	Detent Latching
	Mating Alignment	With
	Lock Type	Latch
	Mating Alignment Type	Latch
Housing Features	Centerline	2.54 mm [.1 in]
	Housing Color	Black
	Housing Material	Thermoplastic
Dimensions	Height	6.604 mm [.26 in]
	Length	12.57 mm [.49 in]

Usage Conditions	Operating Temperature Range (°C)	-65 – 105
Operation/Application	For Use With	Header
Industry Standards	UL Flammability Rating	UL 94V-0
Packaging Features	Packaging Quantity	1
	Packaging Method	Package
Product Compliance	Statement of Compliance PDF VIEW ALL PRODUCT COMPLIANCE	

CUSTOMERS ALSO BOUGHT

WIRE-TO-BOARD CONNECTOR CONTACTS




MTE PIN 22-26 AWG PLTD
5-104505-6

Save to List

Find Similar Products

BARRIER STRIPS




24P.374" DR BARRIER STRIP
2-1546306-4

Save to List

Find Similar Products

WIRE-TO-BOARD CONNECTOR CONTACTS




MTE PIN LP
5-104505-7

Save to List

Find Similar Products

CRIMP RINGS & SPADES



SPG SPADE IS 18-14 6 .030TPBR
60187-2

Save to List

Find Similar Products