



Active

PRODUCT DRAWING
English

3D PDF

TE CONNECTIVITY (TE)

08 SHORT PT RCPT HSG DR .100CL

AMPMODU | AMPMODU IV/V

104482-3

TE Internal Number: 104482-3

Always EU RoHS/ELV Compliant

Centerline **2.54 mm [.1 in]**

Number of Positions **8**

Number of Rows **2**

Row-to-Row Spacing **2.54 mm [.1 in]**

Color **Black**

Product Drawings

[RCPT HSG, DBL ROW, .100x.100 CL SHORT PT, AMPMODU](#)

PDF
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[3D PDF](#)

PDF
3D

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Catalog Pages/Data Sheets

[AMPMODU_INTERCONNECTION_SYSTEM_SECTION5_CONT](#)

PDF
English

Product Specifications

Application Specification

[AMPMODU Short Point Contacts And Housings](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Row-to-Row Spacing

2.54 mm [.1 in]

Connector Type

Housing

Applie To

Wire/Cable

	Applies to	wire/Cable
	Connector Style	Receptacle
	Strain Relief	Without
	Product Type	Connector
<hr/>		
Configuration Features	Number of Positions	8
	Number of Rows	2
<hr/>		
Electrical Characteristics	Dielectric Withstanding Voltage	750 V
	Operating Voltage	300 VAC
	Termination Resistance	12 mΩ
	Insulation Resistance (MΩ)	5000
<hr/>		
Body Features	Color	Black
<hr/>		
Contact Features	Contact Type	Socket
	Contact Current Rating (A)	3
<hr/>		
Termination Features	Termination Method to Wire/Cable	Crimp
<hr/>		
Mechanical Attachment	Mating Retention	Without
	PCB Mount Retention	Without
	Mating Connector Lock	Without
	Panel Mount Retention	Without
	Mating Alignment	Without
<hr/>		
Housing Features	Centerline	2.54 mm [.1 in]
	Housing Configuration	Both Ends Closed
	Housing Color	Black
	Housing Material	Thermoplastic
<hr/>		
Dimensions	Length (in)	.398
	Height (in)	.198
	Wire/Cable Size (AWG)	32 – 20
	Wire/Cable Size (mm ²)	.03 – .6
<hr/>		
Usage Conditions	Operating Temperature Range (°C)	-65 – 105

Flame Retardant

Yes

Operation/Application

For Use With

Contact

Industry Standards

Approved Standards

CSA LR7189, UL E28476

UL Flammability Rating

UL 94V-0

Packaging Features

Packaging Quantity

1

Packaging Method





Package

Product Compliance

[Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

WIRE-TO-BOARD CONNECTOR CONTACTS	BOARD-TO-BOARD HEADERS & RECEPTACLES	SURFACE MOUNT RESISTORS	WIRE-TO-BOARD CONNECTOR HOUSINGS
			
SHORT POINT CONT PLTD SN 1-104480-7	CONT 8-10 AWG PWR, MFBL PLATE 1-1600960-7	RLP73K 2A 1R0 5% 5K RL RLP73K2A1R0JTD	12 MODIV HSG COMP DR .100 POL 3-87977-1
Save to List Find Similar Products	Save to List Find Similar Products	Save to List Find Similar Products	Save to List Find Similar Products