

## **CRIMP RINGS & SPADES**

Ƴ 🖬 f 🔻



✓ Active



TE CONNECTIVITY (TE) SOLIS, R 22-16 M6 Solistrand | Solistrand

130058 TE Internal Number: 130058

Always EU RoHS/ELV Compliant

Terminal Shape **Ring Tongue** 

Stud Diameter 6.3 mm [.248 in ]

Tongue Thickness .79 mm [.031 in]

Sealed  $\operatorname{\textbf{No}}$ 

Heavy Duty No

**Product Drawings** 

TERMINAL, RING TONGUE, SOLISTRAND, WIRE SIZE 22-16 PDF (TIFF AVAILABLE) English

TERMINAL, RING TONGUE, SOLISTRAND, WIRE SIZE 22-16 PDF (TIFF AVAILABLE) English

Please review product documents or **contact us** for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Sealed	No
	Barrel Type	Closed Barrel
	Wire/Cable Type	Regular Wire
	Insulated	No
	Insulated Wire Support	No
	Stud Size	M6
	Shape Code	RING-048
	Wire/Cable Composition	Stranded
Configuration Features	Terminal Angle	Straight
Body Features	Plating Material	Tin
	Plating Thickness	2.54 µm [ 100 µin ]
	Inspection Slot	No

Contact Features	Terminal Shape Terminal Orientation	Ring Tongue Straight
Dimensions	Stud Diameter Tongue Thickness Wire Size (AWG) Wire Size (mm²) Barrel Inside Diameter Material Thickness Overall Length	6.3 mm [ .248 in ] .79 mm [ .031 in ] 22 – 16 .3 – 1.42 1.54 mm [ .061 in ] .81 mm [ .032 in ] 21.84 mm [ .86 in ]
Operation/Application	Heavy Duty	Νο
Industry Standards	Government Qualified	Νο
Packaging Features	Packaging Method Packaging Quantity	Loose Piece 1000
Product Compliance	Statement of Compliance PDF VIEW ALL PRODUCT COMPLIANCE	

## CUSTOMERS ALSO BOUGHT

CRIMP RINGS & SPADES	RIBBON CABLE CONNECTORS	RIBBON CABLE CONNECTORS	SURFACE MOUNT RESISTORS	
	A LEAST BALLES	don moto		
SOLIS SPDFLG 22- 16COM22-18MIL6 323136	IDC LOW PRO HDR 26P RA SHT LAT 1761609-9	A/L UNIV HDR 16P RA LG LAT 5102322-3	3521 22R 1% 2W 352122RFT	>
🔁 Save to List	Save to List	🔁 Save to List	🚝 Save to List	
	Find Similar Products	Find Similar Products	5 Find Similar Products	