





✓ Active



PRODUCT DRAWING



3D PDF

## TE CONNECTIVITY (TE) 70 POS PT CONNECTOR, X2, XENPAK, 30 AU $_{^{\times 2} \mid \times 2}$

1367337-2

TE Internal Number: 1367337-2

Always EU RoHS/ELV Compliant

Product Type Connector

Form Factor X2

PCB Mounting Style **Double-Sided (Belly-to-Belly)** 



**Product Drawings** 

PT CONNECTOR ASSEMBLY, 70 POSITION, RTANG, 0.8MM

PDF **English** 

**CAD Files** 

Customer View Model

2D\_DXF.ZIP English

3D PDF PDF 3D

Customer View Model

3D\_IGS.ZIP English

Customer View Model

3D\_STP.ZIP English

Catalog Pages/Data Sheets

1773408-1 Pluggable Input/Output Solutions Catalog - X2 Section

PDF **English**  **Product Specification** 

Small Form Factor Pluggable, 0.8mm Centerline Connectors

Japanese

Small Form Factor Pluggable, 0.8mm Centerline Connectors

Japanese

SFP 20 Position Connector

PDF Japanese

SFP 20 Position Connector

Japanese

SFP Cage Assemblies

Japanese

SFP Cage Assemblies

PDF Japanese

Small Form Factor Pluggable, 0.8 Mm Centerline Connectors

English

SFP HSSDC II Copper Module Transceiver

Application Specification Small Form-Factor Pluggable (SFP) Connector And Cage Assembly

> PDF English

Qualification Test Report

SFP 20 Position Connector

English

SFP 20 Position Connector

TIF English

Product Environmental Compliance

TE Material Declaration MD\_1367337-2\_080320142357\_dmtec

PDF **English** 

Instruction Sheets

Instruction Sheet (U.S.) Small Form-Factor Pluggable (SFP) Connector And Cage Assembly

PDF **English** 

Please review product documents or contact us for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

**Product Type Features** Product Type Connector

> Form Factor X2

**Printed Circuit Board** Applies To

Connector Style Receptacle

System **X2** 

Contact Features Contact Base Material **Phosphor Bronze** 

> Contact Mating Area Plating Thickness .76 μm [ 29.92 μin ]

Contact Mating Area Plating Material Gold

Termination Features	Termination Method to PC Board	Surface Mount
Mechanical Attachment	PCB Mounting Style	Double-Sided (Belly-to-Belly)
Housing Features	Housing Color Housing Material	Black LCP (Liquid Crystal Polymer)
Industry Standards	UL Flammability Rating	UL 94V-0
Packaging Features	Packaging Method	Таре
Product Compliance	Statement of Compliance	

VIEW ALL PRODUCT COMPLIANCE

