



PC/104 & PC/104 PLUS



Active

PRODUCT DRAWING
English

3D PDF

TE CONNECTIVITY (TE) PC104 CONN NONSTKTHU NO STNDOL AMPMODU

1375963-4
TE Internal Number: 1375963-4

Always EU RoHS/ELV Compliant

Centerline **2.54 mm [.1 in]**

Number of Positions **104**

Number of Loaded Positions **104**

Connector Style **Receptacle**

Product Drawings

[ASSEMBLY, PC/104, NON-STACKTHROUGH CONTACTS, SOLDER](#)
PDF (TIFF AVAILABLE)
English

[ASSEMBLY, PC/104, NON-STACKTHROUGH CONTACTS, SOLDER](#)
PDF (TIFF AVAILABLE)
English

CAD Files

[3D PDF](#)
PDF
English

[Customer View Model](#)
3D_IGS.ZIP
English

[Customer View Model](#)
3D_STP.ZIP
English

[Customer View Model](#)
2D_DXF.ZIP
English

Catalog Pages/Data Sheets

[AMPMODU_INTERCONNECTION_SYSTEM_SECTION1AND2](#)
PDF
English

Product Specifications

Product Specification [PC/104 And PC/104-Plus Connector Systems](#)
PDF
English

Application Specification [PC/104 And PC/104-Plus Connectors](#)
PDF
English

Qualification Test Report [PC/104 And PC/104-Plus Connector Systems](#)
PDF
English

[PC/104 And PC/104-Plus Connector Systems](#)
TIF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Connector Style	Receptacle
	Product Type	Connector
	Board Standoff	Without

Configuration Features	Number of Positions	104
	Number of Loaded Positions	104
	Keyed	No

Electrical Characteristics	Signal Contact Current (A)	3
	Insulation Resistance (MΩ)	1000
	Dielectric Withstanding Voltage (VAC)	500

Contact Features	Contact Base Material	Phosphor Bronze
	Contact Mating Area Plating Material	Gold
	Contact Configuration	Non-Stack Through

Termination Features	Termination Post Length	3.03 mm [.119 in]
----------------------	-------------------------	----------------------------

Mechanical Attachment	PCB Mounting Style	Through Hole
	PCB Mount Retention Type	None

Housing Features	Centerline	2.54 mm [.1 in]
	Housing Material	Nylon - GF
	Housing Color	Black

Usage Conditions	Operating Temperature Range (°C)	-55 – 105
------------------	----------------------------------	------------------













Industry Standards	UL Flammability Rating	UL 94V-0
--------------------	------------------------	-----------------

Other	Comment	See Specific Info Link for information on a PC/104 Extraction Tool., Solder Type
-------	---------	---

Product Compliance [Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

WIRE-TO-BOARD HEADERS & RECEPTACLES	MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES	PC/104 & PC/104 PLUS	HIGH SPEED BACKPLANE CONNECTORS
			
<p>04 MTE HDR SRRA SFMNT .100CL 5-147278-3</p>	<p>02 MODII HDR SRST B/A .100CL 103741-2</p>	<p>PC104 ASY STKTHRU UNKEYED 1375795-2</p>	<p>DC, 7Row, Half Left End, MULTIGIG RT 2R 2102772-1</p>
<p> Save to List  Find Similar Products</p>	<p> Save to List  Find Similar Products</p>	<p> Save to List  Find Similar Products</p>	<p> Save to List  Find Similar Products</p>