



## STANDARD RECTANGULAR CONNECTORS



✓ Active

↓ **PRODUCT DRAWING**  
Japanese

↓ **3D PDF**

TE CONNECTIVITY (TE)

### DYNAMIC D2100 HDR H ASSY 12P X

[Dynamic Series](#) | [Dynamic 2000 Series](#)

1376020-1

TE Internal Number: 1376020-1

Always EU RoHS/ELV Compliant

Product Type **Connector**

Mating Alignment **With**

Mating Alignment Type **Keyed**

Mating Retention **With**

Mating Retention Type **Latch**

#### Product Drawings

[DOUBLE ROW HEADER ASS'Y 12P \(H TYPE\)](#)

PDF (**TIFF AVAILABLE**)  
Japanese

[DOUBLE ROW HEADER ASS'Y 12P \(H TYPE\)](#)

PDF (**TIFF AVAILABLE**)  
Japanese

#### CAD Files

[Customer View Model](#)

2D\_DXF.ZIP  
English

[3D PDF](#)

PDF  
3D

[Customer View Model](#)

3D\_IGS.ZIP  
English

[Customer View Model](#)

3D\_STP.ZIP  
English

#### Catalog Pages/Data Sheets

[D2000 Series Dynamic Connectors](#)

PDF  
English

[1-1773732-4\\_DYNAMIC\\_SERIES\\_CATALOG\\_ENGLISH](#)

PDF  
English

#### Product Specifications

Product Specification

[DYNAMIC CONNECTOR D-2000 SERIES](#)

PDF  
Japanese

#### Product Environmental Compliance

TE Material Declaration

[MD\\_1376020-1\\_02052016137\\_dmtec](#)

PDF  
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Product Type	<b>Connector</b>
	PCB Mounting Orientation	<b>Right Angle</b>
	Sealed	<b>No</b>
	Connector System	<b>Wire-to-Board</b>
	Shielded	<b>No</b>
	Insertion Force	<b>Standard</b>
	Row-to-Row Spacing	<b>3.75 mm [ .147 in ]</b>
	Connector Style	<b>Plug</b>
	Glow Wire Rating	<b>Standard Part - Not Glow Wire</b>
	Strain Relief	<b>Without</b>
	Series Number	<b>2000</b>
	Shrouded	<b>Yes</b>
	Connector Type	<b>Header</b>
	Applies To	<b>Printed Circuit Board</b>
Configuration Features	Number of Positions	<b>12</b>
	Number of Rows	<b>2</b>
	Preloaded	<b>Yes</b>
	Keying	<b>X</b>
	Selectively Loaded	<b>No</b>
Electrical Characteristics	Operating Voltage	<b>250 VAC [ 250 VDC ]</b>
Body Features	Header Type	<b>Shrouded</b>
	Sealable	<b>No</b>
Contact Features	Contact Plating Material	<b>Gold</b>
	Contact Current Rating (A)	<b>5</b>
	Tail Plating Thickness	<b>2 <math>\mu</math>m [ 78.74 <math>\mu</math>m ]</b>
	Multiple Contact Types	<b>Without</b>
	Contact Style	<b>Right Angle</b>
	Contact Type	<b>Tab</b>

	Tail Plating Material	<b>1 in</b>
	Contact Transmits (Typical)	<b>Power, Signal (Data)</b>
	Shunts/Shorting Bars	<b>Without</b>
	Contact Layout	<b>Matrix</b>
Termination Features	Termination Method to PC Board	<b>Through Hole - Solder</b>
Mechanical Attachment	Mating Alignment	<b>With</b>
	Mating Alignment Type	<b>Keyed</b>
	Mating Retention	<b>With</b>
	Mating Retention Type	<b>Latch</b>
	PCB Mount Retention	<b>With</b>
	PCB Mount Retention Type	<b>Retention Leg</b>
	Contact Retention	<b>Without</b>
	PCB Mount Alignment	<b>Without</b>
	Lock Type	<b>Latch</b>
Housing Features	Centerline	<b>2.5 mm [ .098 in ]</b>
	Housing Material	<b>Polyester GF</b>
	Housing Color	<b>Black</b>
Dimensions	PCB Thickness (Recommended)	<b>1.6 mm [ .063 in ]</b>
	Tail Length	<b>3.4 mm [ .134 in ]</b>
	Height	<b>13.2 mm [ .519 in ]</b>
	Width	<b>20.19 mm [ .794 in ]</b>
	Length	<b>17.7 mm [ .696 in ]</b>
Usage Conditions	Operating Temperature Range	<b>-55 – 105 °C [ -67 – 221 °F ]</b>
Operation/Application	For Use With	<b>Receptacle Housing</b>
	Assembly Integration Feature	<b>Without</b>
	Halogen Free	<b>Yes</b>
Industry Standards	UL Flammability Rating	<b>UL 94V-0</b>
	CSA File Number	<b>LR7189</b>
	VDE Tested	<b>No</b>
	CSA Rating	<b>Certified</b>

UL Rating	<b>Recognized</b>
Agency/Standard	<b>CSA, UL</b>
UL File Number	<b>E28476</b>

---

Packaging Features	Packaging Quantity	<b>26</b>
	Packaging Method	<b>Tube, Tube/Box</b>

---

Product Compliance

[Statement of Compliance](#)  
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)