



MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES



Active

PRODUCT DRAWING
English

3D PDF

TE CONNECTIVITY (TE) 02 MODII HDR SRST B/A .100CL

AMPMODU | AMPMODU Headers

146278-2

TE Internal Number: 146278-2

Not EU RoHS or ELV Compliant

[Find Compliant Alternatives](#)

Applies To **Printed Circuit Board**

Connector Style **Plug**

Centerline **2.54 mm [.1 in]**

Number of Positions **2**

Header Type **Breakaway**

Product Drawings

[HEADER ASSEMBLY, MOD II, BREAKAWAY, SINGLE ROW, HIGH TEMPERATURE, VERTICAL, W/.025 SQ. POSTS](#)

PDF
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[3D PDF](#)

PDF
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Applies To

Printed Circuit Board

Connector Style

Plug

PCB Mounting Orientation

Vertical

Connector Type

Header

Row-to-Row Spacing

2.54 mm [.1 in]

Stabilizers

Without

Strain Relief

Without

	Strain Relief	Without
	Board Standoff	With
	Profile	Standard
	Product Type	Connector
	Gasket	Without
<hr/>		
Configuration Features	Number of Positions	2
	Number of Rows	1
	Keyed	No
	Selectively Loaded	No
<hr/>		
Electrical Characteristics	Voltage (VAC)	30
	Dielectric Withstanding Voltage	750 V
<hr/>		
Body Features	Header Type	Breakaway
	Post Size	.64 mm [.025 in]
<hr/>		
Contact Features	Contact Protection	Without
	Contact Shape	Square
	Contact Type	Pin
	Contact Base Material	Phosphor Bronze
	Contact Mating Area Plating Thickness (µin)	100 – 200
	Solder Tail Contact Plating Material	Tin-Lead over Nickel
	Contact Mating Area Plating Material	Tin-Lead
	Contact Current Rating (A)	3
<hr/>		
Termination Features	Termination Post Length	3.05 mm [.12 in]
	Termination End Plating Thickness (µin)	100 – 200
	Termination End Plating Material	Matte Tin-Lead
	Termination Method to PC Board	Surface Mount, Through Hole
<hr/>		
Mechanical Attachment	PCB Mounting Style	Through Hole
	PCB Mount Retention	Without
	Panel Mount Retention	Without
	Mating Alignment	Without
	Mating Connector Lock	Without
<hr/>		

Housing Features	Centerline	2.54 mm [.1 in]
	Housing Color	Black
	Housing Material	LCP (Liquid Crystal Polymer), LCP-GF (Liquid Crystal Polymer)
<hr/>		
Dimensions	PCB Thickness (Recommended)	1.57 mm [.062 in]
	Mating Post Length	5.84 mm [.23 in]
<hr/>		
Usage Conditions	Operating Temperature Range (°C)	-65 – 105
	High Temperature Housing	Yes
<hr/>		
Operation/Application	High Speed Serial Data Connector	No
<hr/>		
Industry Standards	UL Flammability Rating	UL 94V-0
	Approved Standards	CSA LR7189, UL E28476
<hr/>		
Packaging Features	Packaging Quantity	500
	Packaging Method	Carton
<hr/>		
Product Compliance	Statement of Compliance PDF VIEW ALL PRODUCT COMPLIANCE	