



✓ Active

[↓](#) **PRODUCT DRAWING**
English

[↓](#) **3D PDF**

TE CONNECTIVITY (TE)

SEMI HARD TRAY DDR SOCKET 200P

DDR1 and DDR2 SODIMM | 200P

1473006-1

TE Internal Number: 1473006-1

[Converted to EU RoHS/ELV Compliant](#)

DRAM Type **Double Data Rate (DDR)**

Stack Height **5.2 mm [.205 in]**

Module Orientation **Right Angle**

PCB Mounting Style **Surface Mount**

Centerline **.6 mm [.024 in]**

Product Drawings

[DDR1 & DDR2 SODIMM SOCKET 0.6mm PITCH 200POS STANDARD PROFILE REVERSE TYPE](#)

PDF
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[3D PDF](#)

PDF
3D

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Product Specifications

Product Specification

[DDR S.O.DIMM Socket 200 Positions](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_1473006-1_07112013449_dmtec](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

	Profile	Standard
	Row-to-Row Spacing	6.2 mm [.244 in]
	Applies To	Printed Circuit Board
	Product Type	Socket
<hr/>		
Configuration Features	Module Orientation	Right Angle
	Number of Positions	200
	Number of Rows	2
	Number of Bays	2
	Center Key	None
	Keying	Reverse
	Number of Keys	1
<hr/>		
Electrical Characteristics	DRAM Voltage (V)	2.5
<hr/>		
Signal Characteristics	SGRAM Voltage (V)	2.5
<hr/>		
Body Features	Latch Plating Material	Tin
	Ejector Location	Both Ends
	Module Key Type	SGRAM
	Latch Material	Stainless Steel
	Ejector Type	Locking
<hr/>		
Contact Features	Contact Mating Area Plating Material	Gold Flash
	Socket Style	SO DIMM
	Socket Type	Memory Card
	Solder Tail Contact Plating Material	Gold Flash
	Contact Base Material	Copper Alloy
<hr/>		
Termination Features	Insertion Style	Cam-In
<hr/>		
Mechanical Attachment	PCB Mounting Style	Surface Mount
	PCB Mount Retention	With
	PCB Mount Retention Type	Solder Peg
<hr/>		
Housing Features	Centerline	.6 mm [.024 in]
	Housing Color	Black

Housing Material

High Temperature Thermoplastic

Dimensions

Stack Height

5.2 mm [.205 in]

Industry Standards

UL Flammability Rating

UL 94V-0

Packaging Features

Packaging Method

Semi-Hard Tray Assembly

Packaging Quantity





20

Product Compliance

[Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

RECTANGULAR POWER CONNECTORS	SINGLE PHASE FILTERS	SO DIMM SOCKETS	PCB TERMINALS
 07P MTA156 HDR ASSY SQ R/A F/L 640389-7	 2VK3=F7134 S0 2VK3	 SEMI-HARD TRAY ASSY DDR2 SODIMM 5.2H RV 1473150-4	 TAB, P.C.B., .250 SER 1217127-1
Save to List Find Similar Products	Save to List Find Similar Products	Save to List Find Similar Products	Save to List Find Similar Products