



Active

PRODUCT DRAWING
English

3D PDF

TE CONNECTIVITY (TE) SEMI-HARD TRAY DDR2 SODIMM SOCKET 200P 5

DDR1 and DDR2 SODIMM | DDR2 SO DIMM , SO DIMM

1473006-4
TE Internal Number: 1473006-4

- Always EU RoHS/ELV Compliant
- DRAM Type **Double Data Rate (DDR)**
- Stack Height **5.2 mm [.205 in]**
- Module Orientation **Right Angle**
- PCB Mounting Style **Surface Mount**
- Centerline **.6 mm [.024 in]**

Product Drawings

[DDR1 & DDR2 SODIMM SOCKET 0.6mm PITCH 200POS STANDARD PROFILE REVERSE TYPE](#)

PDF
English

CAD Files

[Customer View Model](#)
3D_STP.ZIP
English

[Customer View Model](#)
2D_DXF.ZIP
English

[3D PDF](#)
PDF
3D

[Customer View Model](#)
3D_IGS.ZIP
English

Product Specifications

Product Specification [DDR S.O.DIMM Socket 200 Positions](#)
PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

DRAM Type	Double Data Rate (DDR)
Profile	Standard
Row-to-Row Spacing	6.2 mm [.244 in]
Applies To	Printed Circuit Board

	Product Type	Socket
Configuration Features	Module Orientation	Right Angle
	Number of Positions	200
	Number of Rows	2
	Number of Bays	2
	Center Key	None
	Keying	Reverse
	Number of Keys	1
Electrical Characteristics	DRAM Voltage (V)	1.8
Signal Characteristics	SGRAM Voltage (V)	1.8
Body Features	Latch Plating Material	Tin
	Ejector Location	Both Ends
	Module Key Type	SGRAM
	Latch Material	Stainless Steel
	Ejector Type	Locking
Contact Features	Contact Mating Area Plating Material	Gold Flash
	Socket Style	SO DIMM
	Socket Type	Memory Card
	Solder Tail Contact Plating Material	Gold Flash
	Contact Base Material	Copper Alloy
Termination Features	Insertion Style	Cam-In
Mechanical Attachment	PCB Mounting Style	Surface Mount
	PCB Mount Retention	With
	PCB Mount Retention Type	Solder Peg
Housing Features	Centerline	.6 mm [.024 in]
	Housing Color	Black
	Housing Material	High Temperature Thermoplastic
Dimensions	Stack Height	5.2 mm [.205 in]

Industry Standards

UL Flammability Rating

UL 94V-0

Packaging Features

Packaging Method

Semi-Hard Tray Assembly

Packaging Quantity













20

Product Compliance

[Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

SATA CONNECTORS	BOARD-TO-BOARD HEADERS & RECEPTACLES	RECTANGULAR POWER CONNECTORS	BNC CONNECTORS
			
<p>ASS'Y SATA REC. R/A SMT TYPE 3.45H 2023246-2</p>	<p>0.8FH, P08H.5, 120, 08/Sn, TR, SC 3-5177986-5</p>	<p>2P MICRO MNL HDR ASY SR SIDE L 2029030-2</p>	<p>BNC Ins Str PCB Skt 50Ohm White 1-1337541-0</p>
<p> Save to List  Find Similar Products</p>	<p> Save to List  Find Similar Products</p>	<p> Save to List  Find Similar Products</p>	<p> Save to List  Find Similar Products</p>