



QUICK DISCONNECTS



TE CONNECTIVITY (TE)

110 FASTIN-ON IS

[FASTIN-FASTON](#) | [FASTON Terminals and Housings](#)

160173-2

TE Internal Number: 160173-2

Always EU RoHS/ELV Compliant

Mating Tab Width **2.79 mm [.11 in]**

Mating Tab Thickness **.79 mm [.031 in]**

Wire Insulation Diameter **1.3 – 2 mm [.051 – .078 in]**

Wire Size (AWG) **22 – 20**

Wire Size (mm²) **.3 – .6**

✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

Product Drawings

[.110 SRS FASTIN-ON RECEPTACLE](#)

PDF (**TIFF AVAILABLE**)
English

[.110 SRS FASTIN-ON RECEPTACLE](#)

PDF (**TIFF AVAILABLE**)
English

CAD Files

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

[3D PDF](#)

PDF
3D

[Customer View Model](#)

2D_DXF.ZIP
English

Product Environmental Compliance

TE Material Declaration

[MD_160173-2_06062015346_dmtec](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Wire Stop

No

Disconnect Type

Quick Disconnect

Insertion Force

Normal





	FASTON	Yes
	Wire/Cable Type	Regular Wire
	Insulated	Yes
	Insulated Wire Support	Yes
	Support Style	Insulation Support
	Applies To	Wire/Cable
Configuration Features	Terminal Angle	Straight
	Connection Capacity	Multiple
Body Features	Plating Material	Brass, Tin
	Fully Insulated	Yes
Contact Features	Terminal Orientation	Straight
	Contact Plating Material	Tin
Termination Features	Crimp Type	F-Crimp
Mechanical Attachment	Mating Retention Type	Locking Lance
Dimensions	Mating Tab Width	2.79 mm [.11 in]
	Mating Tab Thickness	.79 mm [.031 in]
	Wire Insulation Diameter	1.3 – 2 mm [.051 – .078 in]
	Wire Size (AWG)	22 – 20
	Wire Size (mm ²)	.3 – .6
	Material Thickness	.25 mm [.01 in]
	Overall Length	14 mm [.551 in]
Operation/Application	For Housing Type	Single or Multiple
Packaging Features	Packaging Method	Reel
	Packaging Quantity	10000
Other	Comment	According to DIN 46340, Part 1

Product Compliance

[Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

CRIMP QUICK DISCONNECTS	SURFACE MOUNT RESISTORS	CRIMP QUICK DISCONNECTS	CRIMP WIRE PINS & TABS
 <p>.110 SRS FASTIN-FASTON TAB 160174-2</p> <p>Save to List Find Similar Products</p>	 <p>CRGH0805 5% 1K0 0.33W CRGH0805J1K0</p> <p>Save to List Find Similar Products</p>	 <p>.250 LIF FASTON REC 100495-2</p> <p>Save to List Find Similar Products</p>	 <p>SHPL REC IS 18-14 .018SPBR 62734-2</p> <p>Save to List Find Similar Products</p>

Products - 5 Results

[View All](#)

[Compare 0/10](#)


Relation Type ▼

RELATIONSHIP

Toolings

Tooling

[See All Toolings](#)


PRODUCT - TOOLINGS		
	<p>Application Tooling - OCEAN Applicators AMP</p> <p>OC-PA-E-FM-055F090F-001-0034 - 2-2150182-1</p> <p>TE INTERNAL NUMBER: 2-2150182-1</p> <p>✓ Active</p>	<p>Not in Scope for EU RoHS/ELV Compliance</p> <p>Region Worldwide</p> <p>Tool Type Applicator</p> <p>Spare Parts Tooling No</p> <p>Applicator Style OCEAN - Pacific</p> <p>Applicator Feed Style End Feed</p>

RELATIONSHIP

Toolings

Tooling

[See All Toolings](#)

PRODUCT - TOOLINGS		
	<p>Application Tooling - OCEAN Applicators AMP</p> <p>OC-055F090F-CRIMPTOOLINGKIT - 7-2150182-7</p> <p>TE INTERNAL NUMBER: 7-2150182-7</p> <p>✓ Active</p>	<p>Not in Scope for EU RoHS/ELV Compliance</p> <p>Region Worldwide</p> <p>Tool Type Applicator</p> <p>Spare Parts Tooling Yes</p> <p>Spare Parts Tool Type Spare</p>

RELATIONSHIP

Toolings
Tooling

[See All Toolings](#)

PRODUCT - TOOLINGS



Application Tooling - OCEAN Applicators
AMP

**OC-AT-E-FA-055F090F-
001-0034 - 2150182-2**

TE INTERNAL NUMBER: 2150182-2

✓ Active

Not in Scope for EU RoHS/ELV
Compliance

Region **Worldwide**

Tool Type **Applicator**

Spare Parts Tooling **No**

Applicator Style **OCEAN -
Atlantic**

Applicator Feed Style **End Feed**

