



TERMINALS & SPLICES

QUICK DISCONNECTS



TE CONNECTIVITY (TE)

250 FASTIN FASTON TAB

[FASTIN-FASTON](#) | [FASTON Terminals and Housings](#)

160691-2

TE Internal Number: 160691-2

Alias ID: AMPS-0-0160691-2, CU3065-000

[Always EU RoHS/ELV Compliant](#)

Terminal Style **Tab**

Mating Tab Width **6.35 mm [.25 in]**

Mating Tab Thickness **.81 mm [.032 in]**

Wire Insulation Diameter (Max) (in) **.125**

Wire Insulation Diameter **2.2 – 3.2 mm [.087 – .126 in]**

✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**



Product Drawings

[250 Ser. Fastin Faston Tab Acc. To Din](#)

PDF (**TIFF AVAILABLE**)

English

[250 Ser. Fastin Faston Tab Acc. To Din](#)

PDF (**TIFF AVAILABLE**)

English

CAD Files

[Customer View Model](#)

3D_IGS.ZIP

English

[Customer View Model](#)

3D_STP.ZIP

English

[3D PDF](#)

PDF

3D

[Customer View Model](#)

2D_DXF.ZIP

English

Catalog Pages/Data Sheets

[1654742_HOUSEHOLD_APPLIANCES_RAST5](#)

PDF

English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Wire Stop	No
	Disconnect Type	Quick Disconnect
	Insertion Force	Normal
	FASTON	Yes
	Wire/Cable Type	Regular Wire
	Insulated	No
	Insulated Wire Support	Yes
	Support Style	Insulation Support
	Applies To	Wire/Cable

Configuration Features	Paired	No
	Stud Hole	Yes
	Terminal Angle	Straight
	Connection Capacity	Single

Body Features	Plating Material	Brass, Tin
	Fully Insulated	No
	Plating Thickness (µin)	40

Contact Features	Terminal Style	Tab
	Terminal Orientation	Straight
	Contact Plating Material	Tin

Termination Features	Crimp Type	F-Crimp
----------------------	------------	----------------

Mechanical Attachment	Mating Retention Type	Locking Lance
	Locking Lance Height (in)	.055

Dimensions	Mating Tab Width	6.35 mm [.25 in]
	Mating Tab Thickness	.81 mm [.032 in]
	Wire Insulation Diameter (Max) (in)	.125
	Wire Insulation Diameter	2.2 – 3.2 mm [.087 – .126 in]

Wire Size (AWG)	22 – 18
Wire Size (mm ²)	.3 – .8
Material Thickness	.4 mm [.016 in]
Overall Length	28 mm [1.1 in]

Operation/Application	For Housing Type	Multiple
-----------------------	------------------	-----------------

Industry Standards	UL Rating	Recognized
	CSA Certified	Yes

Packaging Features	Packaging Method	Reel
	Packaging Quantity	3500

Other	Comment	"According to DIN, except Wire Size Range", Tab for crimping Tab Housing Part No. 927203., With locking hole.
-------	---------	--

Product Compliance	Statement of Compliance PDF
--------------------	--

[VIEW ALL PRODUCT COMPLIANCE](#)

