Our commitment. Your advantage.

Search

Live Product Chat

Check Pricing & Availability

Contact Us About This Product

<u>Product Feature Selector</u>

Search for Tooling

Quick Links

Products

Documentation


Resources

My Account

Customer Support

<u>Home</u> > <u>Products</u> > <u>By Type</u> > <u>Resistors</u> > <u>Product Feature Selector</u> > <u>Product Details</u>

CRG0603F10R Product Details



CRG0603F10R (1622831-1)TE Internal Number: 1622831-1

<u>Active</u>

Fixed Resistors


Converted to EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:


- Resistor Type = General Purpose Resistor
- Resistance Selection = <1K?
- Resistance = 10?
- Power Rating = .10 W
- Tolerance = 1 %

View all Features









Documentation & Additional Information

Product Drawings:

• THICK FILM CHIP RESISTORS SERIES CRG 0603 (PDF, English)

Catalog Pages/Data Sheets:

• Thick Film Precision Chip Resistors - Type CRG Serie... (PDF, English)

Product Specifications:

None Available

Application Specifications:

None Available

Instruction Sheets:

None Available

CAD Files:

None Available

Additional Information:

Product Line Information

Additional Product Images:

• Pad Layout

Related Products:

Tooling

<u>List all Documents</u>

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Resistor Type = General Purpose Resistor
- Resistance (?) = 10
- <u>Element</u> = Thick Film
- Termination Type = Solder

Electrical Characteristics:

- Resistance Selection (?) = <1K
- Power Rating (W) = 0.10
- <u>Tolerance (%)</u> = 1
- Package Type = Taped and Reeled

Body Related Features:

- <u>Series</u> = CRG
- Mount Style = Surface Mount
- Packaging Style = 0603
- Package, Component Size = 1.6×0.8

Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Reflow solder capable to 245?C, Reflow solder capable to 260?C
- RoHS/ELV Compliance History = Converted to comply with RoHS directive

Conditions for Usage:

• Temperature Coefficient (ppm/?C) = ?200

Operation/Application:

• <u>Application</u> = Various

Other:

• Brand = Neohm