Our commitment. Your advantage.

Search

**Live Product Chat** 

Check Pricing & Availability

Contact Us About This Product

<u>Product Feature Selector</u>

Search for Tooling

**Quick Links** 

**Products** 

**Documentation** 


Resources

My Account

**Customer Support** 

<u>Home</u> > <u>Products</u> > <u>By Type</u> > <u>Resistors</u> > <u>Product Feature Selector</u> > <u>Product Details</u>

## CRG0603F2K0 Product Details



CRG0603F2K0 (1622901-1)TE Internal Number: 1622901-1

<u>Active</u>

#### **Fixed Resistors**

Converted to EU RoHS/ELV Compliant (Statement of Compliance)

#### **Product Highlights:**

- Resistor Type = General Purpose Resistor
- Resistance Selection = K?
- Resistance = 2K?
- Power Rating = .10 W
- Tolerance = 1 %


View all Features











# **Documentation & Additional Information**

#### **Product Drawings:**

• THICK FILM CHIP RESISTORS SERIES CRG 0603 (PDF, English)

#### Catalog Pages/Data Sheets:

• Thick Film Precision Chip Resistors - Type CRG Serie... (PDF, English)

#### **Product Specifications:**

None Available

#### **Application Specifications:**

None Available

## **Instruction Sheets:**

None Available

## **CAD Files:**

None Available

## **Additional Information:**

Product Line Information

#### **Additional Product Images:**

• Pad Layout

## **Related Products:**

Tooling

<u>List all Documents</u>

## Product Features (Please use the Product Drawing for all design activity)

## **Product Type Features:**

- Resistor Type = General Purpose Resistor
- Resistance (?) = 2K
- <u>Element</u> = Thick Film
- Termination Type = Solder

## **Electrical Characteristics:**

- Resistance Selection (?) = K
- Power Rating (W) = 0.10
- <u>Tolerance (%)</u> = 1
- Package Type = Taped and Reeled

## **Body Related Features:**

- <u>Series</u> = CRG
- Mount Style = Surface Mount
- Packaging Style = 0603
- Package, Component Size =  $1.6 \times 0.8$

## **Industry Standards:**

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Reflow solder capable to 245?C, Reflow solder capable to 260?C
- RoHS/ELV Compliance History = Converted to comply with RoHS directive

## **Conditions for Usage:**

• Temperature Coefficient (ppm/?C) = ?100

## Operation/Application:

• <u>Application</u> = Various

## Other:

• Brand = Neohm