Our commitment. Your advantage.

Search

Live Product Chat

Check Pricing & Availability

Contact Us About This Product

<u>Product Feature Selector</u>

Search for Tooling

Quick Links

Products

Documentation


Resources

My Account

Customer Support

<u>Home</u> > <u>Products</u> > <u>By Type</u> > <u>Resistors</u> > <u>Product Feature Selector</u> > <u>Product Details</u>

CFR100J150K Product Details



CFR100J150K (1623925-7)

TE Internal Number: 1623925-7

<u>Active</u>

Fixed Resistors

Converted to EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Resistor Type = General Purpose Resistor
- Resistance Selection = K?
- Resistance = 150K ?
- Power Rating = 1.00 W
- Tolerance = 5 %

View all Features



🕒 Add to My Part List 🕡







Documentation & Additional Information

Product Drawings:

• CARBON FILM FIXED RESISTORS SERIES CFR100 (PDF, English)

Catalog Pages/Data Sheets:

• Ceramic Film Fixed Resistors - Type CFR Series - Tyc... (PDF, English)

Product Specifications:

None Available

Application Specifications:

None Available

Instruction Sheets:

None Available

CAD Files:

None Available

Additional Information:

• Product Line Information

Related Products:

Tooling

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Resistor Type = General Purpose Resistor
- <u>Resistance (?)</u> = 150K
- <u>Element</u> = Carbon Film
- <u>Termination Type</u> = Tinned Copper Leads

Electrical Characteristics:

- Resistance Selection (?) = K
- Power Rating (W) = 1.00
- Tolerance (%) = 5
- Package Type = Ammo Packed

Body Related Features:

- <u>Series</u> = CFR100
- Mount Style = Axial Leaded
- <u>Package, Component Size</u> = 12.8 x 4.7

Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Wave solder capable to 240?C, Wave solder capable to 260?C, Wave solder capable to 265?C
- RoHS/ELV Compliance History = Converted to comply with RoHS directive

Conditions for Usage:

• Temperature Coefficient (ppm/?C) = -100 to -500

Operation/Application:

Other:

Brand = Neohm