Our commitment. Your advantage.

Search

Live Product Chat

Check Pricing & Availability

Contact Us About This Product

<u>Product Feature Selector</u>

Search for Tooling

Quick Links

Products

Documentation

Resources

My Account

Customer Support

<u>Home</u> > <u>Products</u> > <u>By Type</u> > <u>Resistors</u> > <u>Product Feature Selector</u> > <u>Product Details</u>

CFR25J330R Product Details



CFR25J330R (1623931-7)

TE Internal Number: 1623931-7

<u>Active</u>

Fixed Resistors

Converted to EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Resistor Type = General Purpose Resistor
- Resistance Selection = <1K?
- Resistance = 330 ?
- Power Rating = .33 W
- Tolerance = 5 %

View all Features









Documentation & Additional Information

Product Drawings:

• CARBON FILM FIXED RESISTORS SERIES CFR25 (PDF, English)

Catalog Pages/Data Sheets:

• Ceramic Film Fixed Resistors - Type CFR Series - Tyc... (PDF, English)

Product Specifications:

None Available

Application Specifications:

None Available

Instruction Sheets:

None Available

CAD Files:

None Available

Additional Information:

• Product Line Information

Related Products:

Tooling

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Resistor Type = General Purpose Resistor
- <u>Resistance (?)</u> = 330
- <u>Element</u> = Carbon Film
- <u>Termination Type</u> = Tinned Copper Leads

Electrical Characteristics:

- Resistance Selection (?) = <1K
- <u>Power Rating (W)</u> = 0.33
- Tolerance (%) = 5
- Package Type = Ammo Packed

Body Related Features:

- <u>Series</u> = CFR25
- Mount Style = Axial Leaded
- <u>Package, Component Size</u> = 6.2 x 2.3

Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Wave solder capable to 240?C, Wave solder capable to 260?C, Wave solder capable to 265?C
- RoHS/ELV Compliance History = Converted to comply with RoHS directive

Conditions for Usage:

<u>Temperature Coefficient (ppm/?C)</u> = -1200 to 0

Operation/Application:

Other:

Brand = Neohm