

Our commitment. Your advantage.

Search

Live Product Chat

Check Pricing & Availability

Contact Us About This Product

<u>Product Feature Selector</u>

Search for Tooling

Quick Links

Documentation

Resources

My Account

Customer Support

<u>Home</u> > <u>Products</u> > <u>By Type</u> > <u>Resistors</u> > <u>Product Feature Selector</u> > <u>Product Details</u>

17PESA474MC19N Product Details



17PESA474MC19N (1624199-9)

TE Internal Number: 1624199-9

Active

Variable Resistors

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Variable Resistor
- Resistor Type = Potentiometer
- Resistance Selection = K?
- Resistance = 470K?
- Power Rating = .25 W

View all Features









Documentation & Additional Information

Product Drawings:

None Available

Catalog Pages/Data Sheets:

• <u>Spindle Operated Potentiometers - Type 17P series - ...</u> (PDF, English)

Product Specifications:

None Available

Application Specifications:

None Available

Instruction Sheets:

None Available

CAD Files:

None Available

Additional Information:

Product Line Information

Related Products:

Tooling

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Type = Variable Resistor
- Resistor Type = Potentiometer
- <u>Resistance (?)</u> = 470K
- <u>Element</u> = Carbon
- <u>Sealed</u> = No
- <u>Mount Angle</u> = Vertical
- <u>Termination Type</u> = PCB Terminations

Electrical Characteristics:

- Resistance Selection (?) = K
- Power Rating (W) = 0.25
- <u>Tolerance (%)</u> = 20

Termination Related Features:

• <u>Termination Post Orientation</u> = In Line

Body Related Features:

- <u>Series</u> = 17P
- Shaft Style = Flatted, 6mm, 5mm A/F
- <u>Package, Component Size</u> = 17mm Sq

Configuration Related Features:

- <u>Sections</u> = Single
- <u>Adjustment Location</u> = Side
- Adjustment Style = Spindle
- Operating Function = Single Turn

Industry Standards:

- Rohs/ELV Compliance = Rohs compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Wave solder capable to 240?C, Wave solder capable to 260?C, Wave solder capable to 265?C
- RoHS/ELV Compliance History = Always was RoHS compliant

Other:

Brand = Citec