




# 170121-1 Product Details

[Share](#) [Print](#) [Email](#)



**170121-1**

## .200" Centerline, 250 V, 13 A max.

Always EU RoHS/ELV Compliant (Statement of Compliance)

### Product Highlights:

- Commercial MATE-N-LOK Product Line
- Wire-to-Wire
- Applies To Wire/Cable
- Contact
- Contact Type = Socket

[View all Features](#)

### Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [View Housings \(69\)](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

TE Internal Number: 170121-1

Active

[View 3D PDF](#)

[Add to My Part List](#) [Request Sample](#) [Find Similar Products](#) [Buy Product](#)

## Documentation & Additional Information

### Product Drawings:

- [MATE-N-LOK SOCKET](#) (PDF, English)

### Catalog Pages/Data Sheets:

- None Available

### Product Specifications:

- None Available

### Application Specifications:

- None Available

### Instruction Sheets:

- None Available

### CAD Files: (CAD Format & Compression Information)

- [2D Drawing](#) (DXF, Version C)
- [3D Model](#) (IGES, Version C)
- [3D Model](#) (STEP, Version C)

[List all Documents](#)

### Additional Information:

- [Product Line Information](#)

### Related Products:

- [Tooling](#)
- [Housings \(69\)](#)

Feedback

## Product Features (Please use the Product Drawing for all design activity)

### Product Type Features:

- Product Line = Commercial MATE-N-LOK
- Product Type = Contact
- Wire/Cable Type = Discrete Wire
- Sealed = No

### Mechanical Attachment:

- Contact Retention = With
- Contact Retention Type = Locking Lance

### Electrical Characteristics:

- Contact - Rated Current (A) = 10 - 20
- Operating Voltage Reference = AC/DC
- Operating Voltage (VAC) = 250
- Operating Voltage (VDC) = 250

### Termination Features:

- Wire/Cable Size (mm<sup>2</sup>) = 0.5 - 2
- Wire/Cable Size (AWG) = 14 - 20
- Termination Method to Wire/Cable = Crimp

### Body Features:

- Wire Type = Stranded

### Contact Features:

- Contact Type = Socket
- Contact Plating, Mating Area, Material = Pre-Tin
- Contact Diameter (mm [in]) = 2.13 [0.084]
- Contact Base Material = Brass

### Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant
- VDE Tested = No

### Environmental:

- Operating Temperature (°C [°F]) = -55 - +105 [-67 - +221]

### Conditions for Usage:

- Applies To = Wire/Cable
- For Multiple Crimp = No
- Accepts Wire Insulation Diameter, Range (mm [in]) = 3.30 [0.130]
- For Use With = Commercial MATE-N-LOK housings

### Operation/Application:

- Application Use = Wire-to-Wire

### Packaging Features:

- Packaging Method = Bag
- Packaging Quantity = 1,000

### Other:

- Brand = AMP

## Corporate Information

[About TE](#)  
[Investors](#)  
[News Room](#)  
[Supplier Portal](#)  
[Careers](#)  
[Terms & Conditions](#)  
[Privacy Policy](#)  
[AODA Accessibility Policy](#)  
[AODA Multi-Year Accessibility Plan](#)

## Quick Links

[Distributor Inventory](#)  
[Product Cross Reference](#)  
[Documents & Drawings](#)  
[Product Compliance Support Center](#)  
[Site Map](#)

## Customer Support

[Email or Chat With Us](#)  
[Find a Phone Number](#)  
[Knowledge Base](#)  
[Manage Your Account](#)

## Keep Me Informed

