



CONNECTORS

## HEADERS & RECEPTACLES



✓ Active

↓ **PRODUCT DRAWING**  
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

### POST HEADER ASSY EI SRS 3POS

[EI Series](#) | [EI Series](#)

171825-3

TE Internal Number: 171825-3

Always EU RoHS/ELV Compliant

Centerline **2.5 mm [ .098 in ]**

Number of Positions **3**

PCB Mounting Orientation **Vertical**

PCB Mounting Style **Through Hole**

Number of Rows **1**



#### Product Drawings

#### [POST HEADER ASSY \(VERTICAL\) AMP EI SERIES CONNECTOR](#)

PDF  
English

#### CAD Files

#### [Customer View Model](#)

2D\_DXF.ZIP  
English

#### [Customer View Model](#)

3D\_STP.ZIP  
English

#### [Customer View Model](#)

3D\_IGS.ZIP  
English

#### [3D PDF](#)

PDF  
English

#### Product Specifications

#### Product Specification

#### [AMP EI Series, Connector](#)

TIF  
Japanese

[AMP EI Series, Connector](#)

[AMP EI Series, Connector](#)PDF  
Japanese[AMP Mass-Termination "EI" Series Connector](#)TIF  
English[AMP Mass-Termination "EI" Series Connector](#)PDF  
English[AMP EI Series Connector](#)PDF  
English[AMP EI Series Connector](#)TIF  
English

Qualification Test Report

---

## Product Environmental Compliance

TE Material Declaration

[MD\\_171825-3\\_02182016156\\_dmtec](#)PDF  
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

---

Product Type Features	PCB Mounting Orientation	<b>Vertical</b>
	Product Type	<b>Connector</b>
	Connector Type	<b>Header</b>
	Strain Relief	<b>Without</b>
	Profile	<b>Low, Standard</b>
	Connector Style	<b>Plug</b>
	Applies To	<b>Printed Circuit Board</b>

---

Configuration Features	Number of Positions	<b>3</b>
	Number of Rows	<b>1</b>
	Number of Positions Applied	<b>3</b>
	Backwall/Post Interruptions	<b>Without</b>

---

Electrical Characteristics	Operating Voltage (VAC)	<b>250</b>
----------------------------	-------------------------	------------

---

Body Features	Header Type	<b>Shrouded</b>
	Circuit	<b>Standard</b>

---

Contact Features	Contact Mating Area Plating Material	<b>Tin over Copper</b>
	Contact Type	<b>Pin</b>
	Solder Tail Contact Plating Material	<b>Tin over Copper</b>
	Contact Termination Area Plating Thickness (µm)	<b>.8</b>

	Contact Current Rating (A)	<b>3.5</b>
	Contact Shape	<b>Square</b>
	Tail Plating Material	<b>Tin</b>
	Contact Termination Area Plating Material	<b>Tin</b>
	Contact Base Material	<b>Brass</b>
Mechanical Attachment	PCB Mounting Style	<b>Through Hole</b>
	PCB Mount Alignment	<b>Without</b>
	Mating Retention	<b>With</b>
	PCB Mount Retention	<b>Without</b>
	Panel Mount Retention	<b>Without</b>
	Contact Retention	<b>Without</b>
	Mating Alignment Type	<b>Polarization</b>
	Mating Alignment	<b>With</b>
	Mating Retention Type	<b>Polarized Lock</b>
Housing Features	Centerline	<b>2.5 mm [ .098 in ]</b>
	Housing Color	<b>Natural</b>
	Housing Material	<b>6/6 Nylon</b>
Dimensions	Tail Length	<b>3.6 mm [ .142 in ]</b>
	Wire/Cable Size (mm <sup>2</sup> )	<b>.08 – .33</b>
	PCB Thickness (Recommended)	<b>1.6 mm [ .063 in ]</b>
	Wire/Cable Size (CMA)	<b>159.8 – 642.4</b>
	Mating Post Length	<b>7.5 mm [ .295 in ]</b>
	Length	<b>7.5 mm [ .295 in ]</b>
	Height	<b>10.4 mm [ .409 in ]</b>
	Wire/Cable Size (AWG)	<b>28 – 22</b>
Usage Conditions	Operating Temperature Range (°C)	<b>-20 – 95</b>
Operation/Application	For Use With	<b>Receptacle Assembly</b>
	Pick and Place Cover	<b>Without</b>
Industry Standards	UL Flammability Rating	<b>UL 94V-0</b>
	CSA Certified	<b>Yes</b>
	RoHS Compliant	<b>Yes</b>

Agency/Standard

**UL**

---

Packaging Features

Packaging Method

**Bag/Box**

Packaging Quantity

**1000**

---

Product Compliance

[Statement of Compliance](#)

PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

