



CONNECTORS

## HEADERS & RECEPTACLES



✓ Active

↓ **PRODUCT DRAWING**  
Japanese

↓ **3D PDF**

TE CONNECTIVITY (TE)

### V-TYPE E.I.S CONN. 2P ASSY

El Series | El Series

172106-2

TE Internal Number: 172106-2

Converted to EU RoHS/ELV Compliant

Centerline **5 mm [ .197 in ]**

Number of Positions **2**

PCB Mounting Orientation **Vertical**

PCB Mounting Style **Through Hole**

Number of Rows **1**



#### Product Drawings

**5mm PITCH POST HEADER ASSY (VERTICAL) AMP EI SERIES CONNECTOR**

PDF (**TIFF AVAILABLE**)

Japanese

**5mm PITCH POST HEADER ASSY (VERTICAL) AMP EI SERIES CONNECTOR**

PDF (**TIFF AVAILABLE**)

Japanese

#### CAD Files

**3D PDF**

PDF  
English

**Customer View Model**

2D\_DXF.ZIP  
English

**Customer View Model**

3D\_IGS.ZIP  
English

**Customer View Model**

3D\_STP.ZIP  
English

#### Product Specifications

Product Specification

AMP EI Series Connector

Product Specification

[AMP EI Series, Connector](#)

TIF  
**Japanese**

[AMP EI Series, Connector](#)

PDF  
**Japanese**

[AMP Mass-Termination "EI" Series Connector](#)

TIF  
**English**

[AMP Mass-Termination "EI" Series Connector](#)

PDF  
**English**

---

Product Environmental Compliance

TE Material Declaration

[MD\\_172106-2\\_09292015121\\_dmtec](#)

PDF  
**English**

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

---

Product Type Features	PCB Mounting Orientation	<b>Vertical</b>
	Product Type	<b>Connector</b>
	Connector Type	<b>Header</b>
	Strain Relief	<b>Without</b>
	Profile	<b>Standard</b>
	Connector Style	<b>Plug</b>
	Applies To	<b>Printed Circuit Board</b>

---

Configuration Features	Number of Positions	<b>2</b>
	Number of Rows	<b>1</b>
	Number of Positions Applied	<b>2</b>
	Backwall/Post Interruptions	<b>Without</b>

---

Electrical Characteristics	Operating Voltage (VAC)	<b>250</b>
----------------------------	-------------------------	------------

---

Body Features	Header Type	<b>Shrouded</b>
	Circuit	<b>Standard</b>

---

Contact Features	Contact Mating Area Plating Material	<b>Tin</b>
	Contact Type	<b>Pin</b>
	Solder Tail Contact Plating Material	<b>Tin</b>
	Contact Current Rating (A)	<b>3.5</b>
	Contact Shape	<b>Square</b>

	Contact Base Material	<b>Brass</b>
Mechanical Attachment	PCB Mounting Style	<b>Through Hole</b>
	PCB Mount Alignment	<b>Without</b>
	Mating Retention	<b>With</b>
	PCB Mount Retention	<b>Without</b>
	Panel Mount Retention	<b>Without</b>
	Contact Retention	<b>Without</b>
	Mating Alignment Type	<b>Polarization</b>
	Mating Alignment	<b>Without</b>
	Mating Retention Type	<b>Polarized Lock</b>
Housing Features	Centerline	<b>5 mm [ .197 in ]</b>
	Housing Color	<b>Natural</b>
	Housing Material	<b>Nylon 6/6</b>
Dimensions	Tail Length	<b>3.6 mm [ .142 in ]</b>
	PCB Thickness (Recommended)	<b>1.6 mm [ .063 in ]</b>
	Mating Post Length	<b>7.5 mm [ .295 in ]</b>
	Length	<b>7.5 mm [ .295 in ]</b>
	Height	<b>10.4 mm [ .409 in ]</b>
Usage Conditions	Operating Temperature Range (°C)	<b>-20 – 95</b>
Operation/Application	For Use With	<b>Receptacle Assembly</b>
	Pick and Place Cover	<b>Without</b>
Industry Standards	UL Flammability Rating	<b>UL 94V-0</b>
Packaging Features	Packaging Method	<b>Bag</b>
	Packaging Quantity	<b>1000</b>
Product Compliance	<a href="#">Statement of Compliance</a> PDF <a href="#">VIEW ALL PRODUCT COMPLIANCE</a>	

