



PCB D-SUB CONNECTORS



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

D-Sub H/D 15Recpt,30u",3.18mm

AMPLIMITE | H , Standard

1734530-3

TE Internal Number: 1734530-3

Always EU RoHS/ELV Compliant

Connector Style **Receptacle**

Centerline (mm) **2.29**

Number of Positions **15**

Number of Rows **3**

Shell Size **1**

Product Drawings

[RECEPTACLE ASSY, SIZE 1,15 POSITION, RIGHT ANGLE,THROUGH HOLE](#)

PDF
English

CAD Files

[Customer View Model](#)

3D_STP.ZIP
English

[Customer View Model](#)

2D_DXF.ZIP
English

[3D PDF](#)

PDF
3D

[Customer View Model](#)

3D_IGS.ZIP
English

Catalog Pages/Data Sheets

[AMPLIMITE Subminiature D Connectors - Right-Angle Posted Connectors](#)

PDF
English

Product Specifications

Application Specification

[AMPLIMITE HD-22 Right-Angle Front Metal Shell Connectors](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_1734530-3_11062015819_dmtec](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Connector Style	Receptacle
	Shell Size	1
	Profile	Standard
	PCB Mounting Orientation	Right Angle
	Grounding Straps	Without
	Shell Type	Front Metal Shell
	Footprint	8.89 mm [.35 in]
	Grounding Indents	Without
	Applies To	Printed Circuit Board
	Sealed	No
Product Type	Connector	

Configuration Features	Number of Positions	15
	Number of Rows	3
	Preloaded	Yes

Body Features	Plastic	No
	Color Code	None
	Shell Plating Material	Nickel
	Color	Black
	Shell Material	SPCC

Contact Features	Solder Tail Contact Plating Material	Tin
	Contact Base Material	Phosphor Bronze
	Contact Mating Area Plating Thickness (µin)	30
	Contact Mating Area Plating Material	Gold

Termination Features	Termination Post Length	3.18 mm [.125 in]
	Grounding Clips	Without

Mechanical Attachment	PCB Mounting Style	Through Hole
	PCB Mount Retention	With
	PCB Mount Retention Type	Boardlocks
	Mating Connector Lock	With
	Mating Connector Lock Type	Female Screwlocks, 4-40 UNC
	Panel Mount Retention	Without

Mating Retention Type	Threaded Inserts
Boardlock Material	Brass
Mating Retention	With
PCB Mount Alignment	With
Mounting Hole Diameter	3.18 mm [.125 in]
Boardlock Plating Material	Tin over Nickel

Housing Features	Centerline (mm)	2.29
	Housing Color	Black
	Housing Material	Thermoplastic

Dimensions	PCB Thickness (Recommended)	1.6 mm [.063 in]
------------	-----------------------------	---------------------------





Industry Standards	UL Flammability Rating	UL 94V-0
--------------------	------------------------	-----------------

Packaging Features	Packaging Method	Tray, Tray/Box
	Packaging Quantity	100

Product Compliance [Statement of Compliance PDF](#)

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

<p>WIRE-TO-BOARD HEADERS & RECEPTACLES</p>  <p>07P MTA100 SHRDED HDR ASSY SN 2-644486-7</p> <p>Save to List Find Similar Products</p>	<p>WIRE-TO-BOARD HEADERS & RECEPTACLES</p>  <p>EP 3W 15R 5% EP3W15RJ</p> <p>Save to List Find Similar Products</p>	<p>WIRE-TO-BOARD HEADERS & RECEPTACLES</p>  <p>08P MTA100 CONN ASSY F/T POL 3-644540-8</p> <p>Save to List Find Similar Products</p>	<p>SURFACE MOUNT RESISTORS</p>  <p>CPF 0603 200K 0.1% 25PPM 1K RL CPF0603B200KE1</p> <p>Save to List Find Similar Products</p>
---	--	---	--