

RJ45 CONNECTORS



PRODUCT DRAWING
English
3D PDF

TE CONNECTIVITY (TE) RJ45,8P8C,SHD,W/O LED,DIP 50u" A-RJ45

1734795-4 TE Internal Number: 1734795-4

Always EU RoHS/ELV Compliant

Port Configuration Single
Shielded Yes
Jack Configuration 1 x 1
Connector Style Jack
Inverted Jack Face Yes

Product Drawings

CAD Files

Customer View Model 3D_IGS.ZIP English

MODULAR JACK, RJ45 8P8C, SHIELD, DIP TYPE

Customer View Model 3D_STP.ZIP English

Customer View Model 2D_DXF.ZIP English

3D PDF PDF 3D

PDF **English**

Please review product documents or **contact us** for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Shielded	Yes
	Connector Style	Jack
	Performance Category	Cat 3
	Profile	Standard
	PCB Mounting Orientation	Side Entry (Right Angle)
	Connector Type	Connector Assembly
	Product Type	Connector
	Jack Type	RJ45

	Grounding Options	PCB Ground
	LED	Without
	Panel Stops	Without
Configuration Features	Port Configuration	Single
	Jack Configuration	1 x 1
	Number of Positions	8
	Number of PCB Ground Tabs	2
	Preloaded	Yes
	Keyed	No
	Panel Ground Location	Top and Side
Body Features	Inverted Jack Face	Yes
	Shield Material	Brass
	Color	Black
	Shield Plating Material	Nickel
Contact Features	Number of Contacts Loaded	8
	Solder Tail Contact Plating Material	Gold Flash over Nickel
	Contact Base Material	Phosphor Bronze
	Contact Mating Area Plating Material	Gold
	Contact Mating Area Plating Thickness (µin)	50
Termination Features	Termination Method to PC Board	Solder
Mechanical Attachment	PCB Mounting Style	Through Hole
	Panel Mount Retention	Without
	Flanged	Νο
Housing Features	Housing Material	PA 9T GF30
	Housing Color	Black
Dimensions	Height	11.3 mm [.444 in]
	PCB Thickness (Recommended)	1.6 mm [.063 in]
	PCB Tail Length	2.4 mm [.094 in]

Industry Standards	UL Flammability Rating	UL 94V-0
Packaging Features	Packaging Quantity Packaging Method	80 Tray, Tray/Box
Product Compliance	Statement of Compliance PDF VIEW ALL PRODUCT COMPLIANCE	

CUSTOMERS ALSO BOUGHT

PCB D-SUB CONNECTORS	CRIMP RINGS & SPADES	ANTENNAS	RADIAL-LEADED DEVICES	
	P			
D-Sub 15P, RCPT, R/A, Dip 1734344-5	TERMINAL, PIDG R IR 12 10 2-36161-3	UAM Assembly 360mm cable 1513472-5	LVR055K-2 LVR055K-2	>
Save to List	Save to List	Save to List	E Save to List	
Find Similar Products	(1) Find Similar Products	Find Similar Products	Find Similar Products	