


# **CONNECTOR HOUSINGS**



✓ Active

**.** 

**PRODUCT DRAWING** Ŧ English 3D PDF

TE CONNECTIVITY (TE) 070 MLC W-W CAP HSG 12P AMP | Multilock Connector System

174933-1 TE Internal Number: 174933-1 Alias ID: 0-0174933-1

#### Always EU RoHS/ELV Compliant

Connector Style Housing for female terminals

Mating Tab Width 1.8 mm [.07 in]

Number of Positions 12

Sealed No

Hybrid Connector No

**Product Drawings** 

.070 SRS MLC 12POS CAP HSG (W-W) PDF (TIFF AVAILABLE) English

.070 SRS MLC 12POS CAP HSG (W-W) PDF (TIFF AVAILABLE) English

CAD Files

3D PDF

PDF **English** 

Customer View Model 3D\_STP.ZIP English

**Customer View Model** 2D\_DXF.ZIP **English** 

**Customer View Model** 3D\_IGS.ZIP **English** 

## **Product Specifications**

**Product Specification** 

Qualification Test Report

.070 SERIES MULTI LOCK I/O CONNECTOR(MLC) PDF Japanese .070 MULTI-LOCK CONNECTOR (WIRE TO WIRE TYPE) PDF English .070 MULTI-LOCK CONNECTOR (WIRE TO WIRE TYPE) TIF English

Please review product documents or contact us for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Ƴ ⊡ f v

Product Type Features	Connector Style	Housing for female terminals		
	Sealed	No		
	Hybrid Connector	No		
	Connector System	Wire-to-Wire		
	Row-to-Row Spacing	3 mm [ .118 in ]		
	Strain Relief	Νο		
Configuration Features	Number of Positions	12		
	Number of Rows	2		
Body Features	Body Material	РВТ		
	Color	White		
Contact Features	Mating Tab Width	1.8 mm [ .07 in ]		
Mechanical Attachment	Terminal Position Assurance	No		
	Mounting Feature	No		
	Polarized	Yes		
Dimensions	Width	18.2 mm [ .717 in ]		
	Height	31.4 mm [ 1.24 in ]		
	Length	32.7 mm [ 1.29 in ]		
Usage Conditions	Operating Temperature (Max) (°C)	70, 75, 80, 85, 90, 100, 105		
	Operating Temperature (Max) (°F)	158, 167, 176, 185, 194, 212, 221		
	Operating Temperature Range	-30 – 105 °C [-22 – 221 °F ]		
Industry Standards	UL Flammability Rating	UL 94-HB		
Packaging Features	Packaging Quantity	50		
Other	Connector Position Assurance Capable	Νο		
Product Compliance				

VIEW ALL PRODUCT COMPLIANCE

# CUSTOMERS ALSO BOUGHT

■				Þ
Find Similar Products	Find Similar Products	Find Similar Products	Find Similar Products	:
E Save to List	🔁 Save to List	📒 Save to List	🔁 Save to List	-   -
16 175030-1	173851-1	SGL 174930-1	18P F/H 176291-1	
070 TAB CONTACT L.P 20-	070 MULTILOCK PLUG 12P	070 MLC W-W CAP HSG 6P	UNIV POWER CAP HSG	>
AUTOMOTIVE, TRUCK, BUS, & OFF-ROAD TERMINALS	AUTOMOTIVE, TRUCK, BUS, & OFF-ROAD HOUSINGS	AUTOMOTIVE, TRUCK, BUS, & OFF-ROAD HOUSINGS	WIRE-TO-BOARD CONNECTOR HOUSINGS	



# Contacts



RELATIONSHIP **Contacts** Identifies Contacts compatible with a given Housing





PRODUCT - CONTACTS

Connectors - Automotive, Truck, Bus, & Off-Road Terminals AMP I Multilock Connector System TAB CONT. (SINGNAL)



✓ Active

### Always EU RoHS/ELV Compliant

Terminal Style **Pin/Tab** Mating Tab Width **1.8 mm** Terminal Transmits **0 – 24 A (Low Power)** Sealed **No** Interface Plating **Tin (Sn)** 

### RELATIONSHIP **Contacts** Identifies Contacts compatible with a given Housing

#### See All Contacts



#### PRODUCT - CONTACTS

Connectors - Automotive, Truck, Bus, & Off-Road Terminals AMP I Multilock .070, Multilock Connector System 070 TAB CONTACT L.P 20-16 - 175030-1

TE INTERNAL NUMBER: 175030-1

✓ Active

## Always EU RoHS/ELV Compliant

Terminal Style **Pin/Tab** 

Mating Tab Width **1.8 mm** 

Terminal Transmits **0 – 24 A (Low** 

Power) Sealed No

Wire Size Search **.5 mm<sup>2</sup>**, **.6 mm<sup>2</sup>**, **.75 mm<sup>2</sup>**, **.85 mm<sup>2</sup>**, **1 mm<sup>2</sup>**, **1.25 mm<sup>2</sup>**