



RIBBON CABLE CONNECTORS



Active

PRODUCT DRAWING
English

3D PDF

TE CONNECTIVITY (TE)

IDC LOW PRO HDR 26P VERT LG LA

AMP-LATCH | Low Profile Headers

1761606-9

TE Internal Number: 1761606-9

Always EU RoHS/ELV Compliant

Centerline **2.54 mm [.1 in]**

PCB Mount Retention **Without**

PCB Mounting Orientation **Vertical**

Termination Method to PC Board **Through Hole**

Shrouded **Yes**

Product Drawings

[HEADER ASSEMBLY, VERTICAL, LONG EJECT LATCH, LOW PROFILE, IDC](#)

PDF
English

CAD Files

[Customer View Model](#)

3D_STP.ZIP
English

[Customer View Model](#)

2D_DXF.ZIP
English

[3D PDF](#)

PDF
3D

[Customer View Model](#)

3D_IGS.ZIP
English

Catalog Pages/Data Sheets

[Ribbon Cable Interconnect Solutions](#)

PDF
English

[7-1773458-6_AMPLATCH_QRG](#)

PDF
English

Product Specifications

Product Specification

[AMP-LATCH And IDC Header Connectors, .100 X .100 Inch Grid](#)

PDF
English

Qualification Test Report

[Connector, AMP-LATCH Header, .100 X .100 Inch Grid](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_1761606-9_122820152118_dmtec](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	PCB Mounting Orientation	Vertical
	Shrouded	Yes
	Row-to-Row Spacing	2.54 mm [.1 in]
	Connector Style	Plug
	Profile	Low
	Applies To	Printed Circuit Board
	Product Type	Connector
	Board Standoff	Without
	Connector Type	Header
	Connector System	Wire-to-Board
Ejection Latches	With	

Configuration Features	Number of Positions	26
	Number of Rows	2





Electrical Characteristics	Operating Voltage (VAC)	250
	Insulation Resistance (M Ω)	1000 – 5000

Body Features	Post Size	.64 mm [.025 in]
	Header Type	Pin Header
	Daisy Chain	With

Contact Features	Contact Mating Area Plating Material	Gold Flash over Palladium Nickel
	Contact Mating Area Plating Thickness	.762 μm [30 μin]
	Contact Shape	Square
	Contact Transmits (Typical)	Signal (Data)
	Solder Tail Contact Plating Material	Tin over Nickel
	Contact Current Rating (A)	1
	Contact Base Material	Phosphor Bronze
	Contact Type	Pin
	Contact Termination Area Plating Material	Tin
	Contact Termination Area Plating Thickness	2.54 μm [100 μin]

Termination Features	Termination Method to PC Board	Through Hole
	Termination Post Length	2.6 mm [.102 in]
Mechanical Attachment	PCB Mount Retention	Without
	Mating Alignment Type	Center
	Mating Connector Lock	Without
	Mating Alignment	With
	Polarization	With
	Panel Mount Retention	Without
	Mating Retention	With
	PCB Mount Alignment	Without
Housing Features	Centerline	2.54 mm [.1 in]
	Housing Color	Black
	Housing Style	4-Sided
	Housing Entry Style	Top
	Housing Material	PBT
Dimensions	Height	9.19 mm [.36 in]
	Length	40.64 mm [1.6 in]
	Shrouded End Dimension	3.76 mm [.148 in]
Usage Conditions	Temperature Rating	High
	Operating Temperature Range (°C)	-65 – 105
Operation/Application	For Use With	AMP-Latch Receptacle
Industry Standards	UL Flammability Rating	UL 94V-0
Packaging Features	Packaging Method	Tube
	Packaging Quantity	13
Product Compliance	Statement of Compliance PDF VIEW ALL PRODUCT COMPLIANCE	

CUSTOMERS ALSO BOUGHT

<p>SURFACE MOUNT RESISTORS</p>  <p>CRGH2512 5% 27K 2W CRGH2512J27K</p> <p>Save to List Find Similar Products</p>	<p>BOARD-TO-BOARD HEADERS & RECEPTACLES</p>  <p>20 MODII 2PC HDR DR W/HLDWN, ROHS 5-534978-3</p> <p>Save to List Find Similar Products</p>	<p>WIRE-TO-BOARD HEADERS & RECEPTACLES</p>  <p>10 MTE HDR SRRA LATCH .100CL 103635-9</p> <p>Save to List Find Similar Products</p>	<p>WIRE-TO-BOARD HEADERS & RECEPTACLES</p>  <p>02 MTE HDR SRST LATCH .100CL 103638-1</p> <p>Save to List Find Similar Products</p>
--	--	--	--

Products - 13 Results

[View All](#)

Compare 0/10



Relation Type

RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)


	<p>PRODUCT - MATING PRODUCTS</p> <p>Connectors - Ribbon Cable Connectors 1 AMP-LATCH - NOVO</p> <p>609-2630LF FEM SOCKET, LEAD FREE - 1-1658526-5</p> <p>TE INTERNAL NUMBER: 1-1658526-5</p> <p>Always EU RoHS/ELV Compliant</p> <p>Number of Positions 26</p> <p>Connector Style Receptacle</p> <p>Active</p>
	<p>PRODUCT - MATING PRODUCTS</p> <p>Connectors - Ribbon Connector Accessories AMP-LATCH AMP-LATCH - NOVO</p> <p>609-2631HD=FSKT IDC S 26 SR - 1-1437021-2</p> <p>TE INTERNAL NUMBER: 1-1437021-2 ALIAS ID: 609-2631HD</p> <p>Always EU RoHS/ELV Compliant</p> <p>Accessory Type Strain Relief</p> <p>Number of Positions 26</p> <p>Active</p>

RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

	<p>PRODUCT - MATING PRODUCTS</p> <p>Connectors - Ribbon Cable Connectors 1 AMP-LATCH - NOVO</p> <p>622-2641LF FEM SOCKET, LEAD FREE - 1-1658527-0</p> <p>TE INTERNAL NUMBER: 1-1658527-0</p> <p>Always EU RoHS/ELV Compliant</p> <p>Number of Positions 26</p> <p>Connector Style Receptacle</p> <p>Active</p>
---	---

RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

PRODUCT - MATING PRODUCTS



Connectors - Ribbon Connector Accessories
AMP-LATCH | AMP-LATCH - NOVO

026 STRAIN RELIEF A-L RCPT - 499252-3

TE INTERNAL NUMBER: 499252-3
ALIAS ID: 1108432

✓ Active

Always EU RoHS/ELV Compliant

Accessory Type **Strain Relief**

PRODUCT - MATING PRODUCTS



Connectors - Ribbon Cable Connectors
AMP-LATCH | AMP-LATCH - NOVO

26 NOVO MIL/CTR 30DP, LEAD FREE - 1658622-6

TE INTERNAL NUMBER: 1658622-6

✓ Active

Always EU RoHS/ELV Compliant

Centerline **2.54 mm**

PCB Mount Retention **Without**

PCB Mounting Orientation

Vertical

Termination Method to PC Board

Through Hole - Solder

Termination Method to

Wire/Cable **Insulation**

Displacement Crimp (IDC)