



1775134-1 Product Details

[Share](#) | [Print](#) | [Email](#)


1775134-1

PCB Mounted Jacks - Single Port, Multi-port and Stacked

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Connector
- Preloaded
- Single Port Configuration
- 1 x 1 Jack Configuration
- Jack Type = RJ45

[View all Features](#)

Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

TE Internal Number: 1775134-1

Active
[Add to My Part List](#) | [Request Sample](#) | [Find Similar Products](#) | [Buy Product](#)

Documentation & Additional Information	
<p>Product Drawings:</p> <ul style="list-style-type: none"> • MODULAR JACK, RJ45, SINGLE (PDF, English) <p>Catalog Pages/Data Sheets:</p> <ul style="list-style-type: none"> • None Available <p>Product Specifications:</p> <ul style="list-style-type: none"> • None Available <p>Application Specifications:</p> <ul style="list-style-type: none"> • None Available <p>Instruction Sheets:</p> <ul style="list-style-type: none"> • None Available <p>CAD Files:</p> <ul style="list-style-type: none"> • None Available 	<p>Additional Information:</p> <ul style="list-style-type: none"> • Product Line Information <p>Related Products:</p> <ul style="list-style-type: none"> • Tooling

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

<p>Product Type Features:</p> <ul style="list-style-type: none"> • Product Type = Connector • Jack Type = RJ45 • PCB Mounting Orientation = Side Entry (Right Angle) • PCB Mount Style = Through Hole • Performance Category = Cat 3 • LED = Without • Grounding Options = Panel Ground and PCB Ground • Panel Stops = Without • Keyed = No • Profile = Standard • Color = Black <p>Mechanical Attachment:</p> <ul style="list-style-type: none"> • Panel Mount Retention = Without <p>Termination Features:</p> <ul style="list-style-type: none"> • Termination Method to PC Board = Solder <p>Dimensions:</p> <ul style="list-style-type: none"> • Height (mm [in]) = 13.25 [0.522] • PCB Tail Length (mm [in]) = 2.62 [0.103] • PCB Thickness, Recommended (mm [in]) = 1.57 [0.062] <p>Body Features:</p> <ul style="list-style-type: none"> • Inverted Jack Face = Yes • Shield Plating = Nickel • Shield Material = Brass 	<p>Contact Features:</p> <ul style="list-style-type: none"> • Solder Tail Contact Plating = Gold Flash over Nickel • Contact Plating, Mating Area, Material = Gold (6) • Contact Base Material = Phosphor Bronze <p>Housing Features:</p> <ul style="list-style-type: none"> • Housing Material = High Temperature Thermoplastic <p>Configuration Features:</p> <ul style="list-style-type: none"> • Preloaded = Yes • Port Configuration = Single • Jack Configuration = 1 x 1 • Number of Positions = 8 • Shielded = Yes • Number of PCB Ground Tabs = 2 <p>Industry Standards:</p> <ul style="list-style-type: none"> • RoHS/ELV Compliance = RoHS compliant, ELV compliant • Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C • RoHS/ELV Compliance History = Always was RoHS compliant • UL Flammability Rating = UL 94V-0 <p>Packaging Features:</p> <ul style="list-style-type: none"> • Packaging Method = Tray <p>Product Availability:</p> <ul style="list-style-type: none"> • Region = Asia <p>Other:</p> <ul style="list-style-type: none"> • Brand = TE Connectivity
---	---

Corporate Information

[About TE](#)
[Investors](#)
[News Room](#)
[Supplier Portal](#)
[Careers](#)
[Terms & Conditions](#)
[Privacy Policy](#)
[AODA Accessibility Policy](#)
[AODA Multi-Year Accessibility Plan](#)

Quick Links

[Distributor Inventory](#)
[Product Cross Reference](#)
[Documents & Drawings](#)
[Product Compliance Support Center](#)
[Site Map](#)

Customer Support

[Email or Chat With Us](#)
[Find a Phone Number](#)
[Knowledge Base](#)
[Manage Your Account](#)

Keep Me Informed

