



## CONNECTOR HOUSINGS



✓ Active

↓ **PRODUCT DRAWING**  
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

### DYNAMIC D-3 W-T-W TAB HSG 20P

[Dynamic Series](#) | [Dynamic 3000 Series](#)

178803-8

TE Internal Number: 178803-8

Always EU RoHS/ELV Compliant

Connector System **Wire-to-Panel, Wire-to-Wire**

Centerline **3.81 mm [ .1499 in ]**

Row-to-Row Spacing **5.08 mm [ .2 in ]**

Number of Positions **20**

Number of Rows **2**

#### Product Drawings

[WIRE TO WIRE PANEL MOUNT TYPE TAB HSG FOR DYNAMIC 3100](#)

PDF  
English

#### CAD Files

[Customer View Model](#)

2D\_DXF.ZIP  
English

[Customer View Model](#)

3D\_IGS.ZIP  
English

[Customer View Model](#)

3D\_STP.ZIP  
English

[3D PDF](#)

PDF  
English

#### Catalog Pages/Data Sheets

[D3000 Series Dynamic Connectors](#)

PDF  
English

[1-1773732-4\\_DYNAMIC\\_SERIES\\_CATALOG\\_ENGLISH](#)

PDF  
English

#### Product Specifications

Product Specification

[Dynamic Connector D-3000 Series](#)

TIF  
Japanese

[Dynamic Connector D-3000 Series](#)

PDF  
Japanese

Product Type Features	Connector System	<b>Wire-to-Panel, Wire-to-Wire</b>
	Row-to-Row Spacing	<b>5.08 mm [ .2 in ]</b>
	Connector Style	<b>Plug</b>
	Sealed	<b>No</b>
	Applies To	<b>Panel, Wire/Cable</b>
	Series Number	<b>3000</b>
	Glow Wire Rating	<b>Standard Part - Not Glow Wire</b>
	Product Type	<b>Connector</b>
Connector Type	<b>Housing</b>	
Configuration Features	Number of Positions	<b>20</b>
	Number of Rows	<b>2</b>
	Selectively Loaded	<b>No</b>
	Preloaded	<b>No</b>
Electrical Characteristics	Operating Voltage	<b>250 VAC [ 250 VDC ]</b>
Body Features	Sealable	<b>No</b>
Contact Features	Contact Type	<b>Tab</b>
	Contact Layout	<b>Matrix</b>
	Shunts/Shorting Bars	<b>Without</b>
	Multiple Contact Types	<b>Without</b>
Mechanical Attachment	Panel Mount Retention Type	<b>Screw Mount</b>
	Panel Mount Retention	<b>With</b>
Housing Features	Centerline	<b>3.81 mm [ .1499 in ]</b>
	Housing Material	<b>Polyester GF</b>
	Housing Color	<b>Black</b>
Dimensions	Length	<b>67 mm [ 2.637 in ]</b>
	Height	<b>33.6 mm [ 1.322 in ]</b>
	Width	<b>17.78 mm [ .699 in ]</b>
Usage Conditions	Operating Temperature Range	<b>-55 – 105 °C [ -67 – 221 °F ]</b>

Operation/Application	Halogen Free	<b>Yes</b>
	For Use With	<b>Receptacle Housing</b>

Industry Standards	CSA Rating	<b>Certified</b>
	CSA File Number	<b>LR7189</b>
	UL Rating	<b>Recognized</b>
	CSA Certified	<b>Yes</b>
	VDE Tested	<b>No</b>
	UL File Number	<b>E28476</b>
	Agency/Standard	<b>CSA, UL</b>
	UL Flammability Rating	<b>UL 94V-0</b>

Packaging Features	Packaging Quantity	<b>100</b>
	Packaging Method	<b>Bag</b>

Product Compliance [Statement of Compliance PDF](#)  
[VIEW ALL PRODUCT COMPLIANCE](#)

## CUSTOMERS ALSO BOUGHT

<p><b>AUTOMOTIVE, TRUCK, BUS, &amp; OFF-ROAD TERMINALS</b></p> <p><b>0.64III RCPT NON SEALED (TYPE1)</b> 1674311-1</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>	<p><b>RECTANGULAR CONNECTOR HOUSINGS</b></p> <p><b>DYNAMIC D-3200S TAB HSG 4P K/Y</b> 2-179552-4</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>	<p><b>I/O CONNECTOR CONTACTS</b></p> <p><b>3.81 DYNAMIC TAB LP TN 20-16</b> 175289-5</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>	<p><b>I/O CONNECTOR CONTACTS</b></p> <p><b>DYNAMIC D-3 TAB L/P 3L 16-14</b> 353718-3</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>
--	--	--	--

Products - 30 Results

[View All](#) [Compare 0/10](#)

Relation Type ▼

RELATIONSHIP

## Contacts

Identifies Contacts compatible with a given Housing

[See All Contacts](#)

### PRODUCT - CONTACTS



Connectors - I/O Connector Contacts  
Dynamic Series | Dynamic 3000 Series

## DYNAMIC D-3 TAB CONT. S 28-24 - 175284-2

TE INTERNAL NUMBER: 175284-2

✓ Active

Always EU RoHS/ELV Compliant

Contact Type **Tab**

Contact Mating Area Plating

Material **Gold**

Operating Voltage **250 VAC, 600 VAC**

Contact Retention **With**

Contact Retention Type **Locking Lance**



RELATIONSHIP

## Contacts

Identifies Contacts compatible with a given Housing

[See All Contacts](#)

### PRODUCT - CONTACTS



Connectors - I/O Connector Contacts  
Dynamic Series | Dynamic 3000 Series

## DYNAMIC D-3 TAB CONT 3L 16-14 - 353716-2

TE INTERNAL NUMBER: 353716-2

✓ Active

Always EU RoHS/ELV Compliant

Contact Type **Tab**

Contact Mating Area Plating

Material **Gold**

Operating Voltage **250 VAC, 600 VAC**

Contact Retention **With**

Contact Retention Type **Locking Lance**



RELATIONSHIP

## Contacts

Identifies Contacts compatible with a given Housing

[See All Contacts](#)

### PRODUCT - CONTACTS



Connectors - I/O Connector Contacts  
Dynamic Series | Dynamic 3000 Series

## DYNAMIC D-3 TAB CONT 2L 16-14 - 917485-2

TE INTERNAL NUMBER: 917485-2

✓ Active

Always EU RoHS/ELV Compliant

Contact Type **Tab**

Contact Mating Area Plating

Material **Gold**

Operating Voltage **250 VAC, 600 VAC**

Contact Retention **With**

Contact Retention Type **Locking Lance**

