




CONNECTORS

## WIRE-TO-BOARD CONNECTOR CONTACTS



✓ Active

↓ **PRODUCT DRAWING**  
English

↓ **3D PDF**

### TE CONNECTIVITY (TE) MOD 2 TERMINAL AMPMODU | AMPMODU IV/V

182206-2  
TE Internal Number: 182206-2

Always EU RoHS/ELV Compliant

Contact Type **Socket**

Wire/Cable Size (AWG) **26 – 22**

Wire/Cable Size (mm<sup>2</sup>) **.12 – .4**

Contact Mating Area Plating Material **Pre-Tin**

Packaging Method **Loose Piece**



### Product Drawings

[Ampmodu Ii Rec Contact High Pressure C.O.S.I.](#)  
PDF (TIFF AVAILABLE)  
English

[Ampmodu Ii Rec Contact High Pressure C.O.S.I.](#)  
PDF (TIFF AVAILABLE)  
English

### CAD Files

[Customer View Model](#)  
3D\_IGS.ZIP  
English

[Customer View Model](#)  
3D\_STP.ZIP  
English

[Customer View Model](#)  
2D\_DXF.ZIP  
English

[3D PDF](#)  
PDF  
English

### Product Specifications

[Application Specification](#)

[AMPMODU Mod II Interconnects Custom Beveled Contact](#)

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Wire/Cable Type	<b>Discrete Wire</b>
	Product Type	<b>Contact</b>
	Applied Pressure	<b>Standard</b>
	With Insulation Support	<b>Yes</b>
	Applies To	<b>Wire/Cable</b>
Contact Features	Contact Type	<b>Socket</b>
	Contact Mating Area Plating Material	<b>Pre-Tin</b>
	Contact Base Material	<b>Phosphor Bronze</b>
	Contact Mating Area Plating Thickness (µm)	<b>.8</b>
Termination Features	Termination Method to Wire/Cable	<b>Crimp</b>
	Crimp Area Plating Thickness (µm)	<b>.8</b>
	Crimp Area Plating Material	<b>Tin</b>
Dimensions	Wire/Cable Size (AWG)	<b>26 – 22</b>
	Wire/Cable Size (mm <sup>2</sup> )	<b>.12 – .4</b>
	Insulation Diameter	<b>.89 – 1.55 mm [ .035 – .061 in ]</b>
Packaging Features	Packaging Method	<b>Loose Piece</b>
	Packaging Quantity	<b>2000</b>
Product Compliance	<p><a href="#">Statement of Compliance</a> PDF</p> <p><a href="#">VIEW ALL PRODUCT COMPLIANCE</a></p>	



