



RECTANGULAR POWER CONNECTORS



TE CONNECTIVITY (TE)

5mm B-T-W Conn. 2P HDR ASSEMBL

AMP | Power Double Lock

2-1376382-3

TE Internal Number: 2-1376382-3

Always EU RoHS/ELV Compliant

Product Type **Header**

Housing Type **Receptacle**

Connector System **Wire-to-Board**

Applies To **Printed Circuit Board**

Contact Current Rating (A) **10**

Active

PRODUCT DRAWING
English

3D PDF

Product Drawings

[5.0 POWER KEY CONNECTOR 2P HEADER ASSEMBLY](#)

PDF
English

CAD Files

[3D PDF](#)

PDF
3D

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Catalog Pages/Data Sheets

[SOFT_SHELL_PIN_SOCKET_CONNECTORS_STANDARD_DENSITY](#)

PDF
English

Product Specifications

Product Specification

[5.0 POWER KEY CONNECTOR](#)

PDF
English

Application Specification

[5.0 POWER KEY CONNECTOR](#)

PDF
Japanese

Qualification Test Report

[5.0 POWER KEY CONNECTOR](#)

TIF
Japanese

[5.0 PKC QUALIFICATION TEST REPORT](#)

PDF
Japanese

[5.0 PKC QUALIFICATION TEST REPORT](#)

TIF
Japanese

Product Environmental Compliance

TE Material Declaration

[MD_2-1376382-3_052420152334_dmtec](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Product Type	Header
	Housing Type	Receptacle
	Contact Type	Pin, Tab
	Header Type	Shrouded

Configuration Features	Number of Positions	2
	Centerline	5 mm [.197 in]
	PCB Mounting Orientation	Vertical
	Number of Rows	1
	Contact Layout	Inline

Electrical Characteristics	Contact Current Rating (A)	10
	Operating Voltage (VAC)	300

Contact Features	Contact Termination Area Plating Material	Tin
	Contact Mating Area Plating Material	Tin
	Contact Mating Area Plating Thickness	1 μm [39.37 μin]
	Contact Base Material	Copper Alloy
	Contact Termination Area Plating Thickness	1 μm [39.37 μin]













Termination Features	Termination Method to PC Board	Through Hole - Press-Fit
	Termination Post/Tail Length	3.5 mm [.138 in]

Mechanical Attachment	Mating Alignment	Without
	Mating Retention	With
	PCB Mount Retention	With
	PCB Mount Retention Type	Mounting Post/Kinked Legs
	PCB Mount Alignment	Without
	Mating Retention Type	Latch

Housing Features	UL Flammability Rating	UL 94V-0
	Housing Color	Blue
	Housing Material	Nylon 6/6 GF
<hr/>		
Dimensions	Mating Post Length	6.3 mm [.248 in]
	Width	14.1 mm [.555 in]
	Height	14.1 mm [.55 in]
	PCB Thickness (Recommended)	1.6 mm [.063 in]
	Length	11.6 mm [.456 in]
<hr/>		
Usage Conditions	Sealed Condition	Not Sealed
<hr/>		
Operation/Application	Connector System	Wire-to-Board
	Applies To	Printed Circuit Board
	Operating Temperature	-30 – 105 °C [-22 – 221 °F]
	Circuit Application	Signal/Power
<hr/>		
Industry Standards	Glow Wire Rating	Standard Part - Not Glow Wire
	Agency/Standard Number	E28476
	UL Rating	Recognized
	CSA File Number	LR7189
	Agency/Standard	CSA, UL
<hr/>		
Packaging Features	Packaging Method	Bag
	Packaging Quantity	100
<hr/>		
Other	For Use With	Plug Housing
	Selectively Loaded	No
<hr/>		
Product Compliance	Statement of Compliance PDF VIEW ALL PRODUCT COMPLIANCE	

CUSTOMERS ALSO BOUGHT

<p>WIRE-TO-BOARD HEADERS & RECEPTACLES</p> 	<p>STANDARD POWER RELAYS</p> 	<p>WIRE-TO-BOARD HEADERS & RECEPTACLES</p> 	<p>RECTANGULAR POWER CONNECTORS</p> 
------------------------------------------------------------------------------------------------------------------------------------	------------------------------------------------------------------------------------------------------------------	------------------------------------------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------------------------------

 <p>2.5 SIGNAL D/LOCK HDR ASSY 12P 917732-1</p>	 <p>OJ-SH-112HM, 000 OJ-SH-112HM,000</p>	 <p>2.5 SIGNAL D/LOCK HDR ASSY 3P 917723-1</p>	 <p>GIC 3.3 PLUG HOUSING 8P 1827387-1</p>
<p> Save to List</p> <p> Find Similar Products</p>	<p> Save to List</p> <p> Find Similar Products</p>	<p> Save to List</p> <p> Find Similar Products</p>	<p> Save to List</p> <p> Find Similar Products</p>

Products - 1 Results

[View All](#)

[Compare 0/10](#)

Relation Type ▼

RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

PRODUCT - MATING PRODUCTS



Connectors - Rectangular Power Connectors
AMP I Power Double Lock

**5MM POWER KEY 2P
PLUG HSG BLUE**
- 2-1376388-3

TE INTERNAL NUMBER: 2-1376388-3

✓ Active

Always EU RoHS/ELV Compliant

Product Type **Housing**

Housing Type **Plug**

Connector System **Wire-to-Board**

Applies To **Wire/Cable**

Contact Current Rating **10 A**

