



RGP0207CHJ430M Product Details

[Share](#) | [Print](#) | [Email](#)


RGP0207CHJ430M

(2-1623708-0)

TE Internal Number: 2-1623708-0

Active

Fixed Resistors

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Fixed Resistor
- Resistor Type = High Value/High Voltage Resistors
- Resistance Selection = M Ω
- Resistance = 430M Ω
- Power Rating = .25 W

[View all Features](#)

Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

[Add to My Part List](#) | [Request Sample](#) | [Find Similar Products](#) | [Buy Product](#)

Documentation & Additional Information

Product Drawings:

- [METAL GLAZE FIXED RESISTORS STYLE RGP0207CH](#) (PDF, English)

Catalog Pages/Data Sheets:

- [1309350_PASSIVE_COMPONENT](#) (PDF, English)
- [Metal Glaze Fixed Resistors - Type RGP Series - Tyco...](#) (PDF, English)
- [4-1773460-6_RESISTIVE_SOLUTIONS_RAIL](#) (PDF, English)
- [8-1773459-4_POWER_FILTERING_AND_RESISTIVE_SOLUTIONS_...](#) (PDF, English)

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

[List all Documents](#)

Feedback

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Type = Fixed Resistor
- Resistor Type = High Value/High Voltage Resistors
- Element = Thick Film

Electrical Characteristics:

- Resistance Selection (Ω) = M
- Resistance (Ω) = 430M
- Power Rating (W) = 0.25
- Tolerance (%) = 5

Termination Features:

- Termination Type = Tinned Copper Leads

Body Features:

- Mount Style = Axial Leaded
- Package, Component Size = 6.5 x 2.5

Configuration Features:

- Number of Terminations = 2
- Number of Resistors = 1

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

- [Temperature Coefficient \(ppm/°C\)](#) = ± 350

Operation/Application:

- [Application](#) = High Voltage

Packaging Features:

- [Package Type](#) = Ammo Packed

Other:

- [Series](#) = RGP
- Brand = Neohm

[News Room](#)

[Supplier Portal](#)

[Careers](#)

[Terms & Conditions](#)

[Privacy Policy](#)

[AODA Accessibility Policy](#)

[AODA Multi-Year Accessibility
Plan](#)

[Documents & Drawings](#)

[Product Compliance Support Center](#)

[Site Map](#)

[Knowledge Base](#)

[Manage Your Account](#)

