**Live Product Chat** 

Check Pricing & Availability

Contact Us About This Product



Our commitment. Your advantage.

Search

**Quick Links** 

Search for Tooling Product Feature Selector

**Products** 

**Documentation** 

Resources

**My Account** 

**Customer Support** 

<u>Home</u> > <u>Products</u> > <u>By Type</u> > <u>Resistors</u> > <u>Product Feature Selector</u> > <u>Product Details</u>

# SBCHE1547RJ Product Details



SBCHE1547RJ (2-1623729-1)

TE Internal Number: 2-1623729-1



#### **Fixed Resistors**

Converted to EU RoHS/ELV Compliant (Statement of Compliance)

#### **Product Highlights:**

- Resistor Type = Power Resistor
- Resistance Selection = <1K?
- Resistance = 47?
- Power Rating = 17.00 W
- Tolerance = 5 %

View all Features







#### **Documentation & Additional Information**

### **Product Drawings:**

None Available

# Catalog Pages/Data Sheets:

• High Power Resistor - Type SBC (Square Ceramic) Seri... (PDF, English)

# **Product Specifications:**

None Available

## **Application Specifications:**

None Available

#### **Instruction Sheets:**

• None Available

## **CAD Files:**

None Available

### **Additional Information:**

• Product Line Information

#### **Related Products:**

• Tooling

List all Documents

# Product Features (Please use the Product Drawing for all design activity)

#### **Product Type Features:**

- Resistor Type = Power Resistor
- Resistance (?) = 47
- **Element** = Wirewound
- <u>Termination Type</u> = Tinned Copper Leads

### **Electrical Characteristics:**

- Resistance Selection (?) = <1K
- Power Rating (W) = 17.00
- Tolerance (%) = 5
- Package Type = Loose Piece Box

# **Body Related Features:**

- <u>Series</u> = SBC
- Mount Style = Axial Leaded
- Package, Component Size = 9 x 10 x 75

# **Industry Standards:**

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Wave solder capable to 240?C, Wave solder capable to 260?C, Wave solder capable to 265?C
- RoHS/ELV Compliance History = Converted to comply with RoHS directive

#### **Conditions for Usage:**

• Temperature Coefficient (ppm/?C) = ?200

# Operation/Application:

• Application = Power

### Other:

• Brand = CGS