




RIBBON CABLE CONNECTORS



TE CONNECTIVITY (TE)

IDC LOW PRO HDR 26P VERT BLUE

AMP-LATCH | Low Profile Headers

2-1761603-9

TE Internal Number: 2-1761603-9

Always EU RoHS/ELV Compliant

Centerline **2.54 mm [.1 in]**

PCB Mount Retention **Without**

PCB Mounting Orientation **Vertical**

Termination Method to PC Board **Through Hole**

Shrouded **Yes**

Active

PRODUCT DRAWING
English

3D PDF

Product Drawings

[HEADER ASSEMBLY, VERTICAL, LOW PROFILE, IDC](#)

PDF
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

[3D PDF](#)

PDF
English

Product Specifications

Product Specification

[AMP-LATCH And IDC Header Connectors, .100 X .100 Inch Grid](#)

PDF
English

Qualification Test Report

[Connector, AMP-LATCH Header, .100 X .100 Inch Grid](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_2-1761603-9_02122016857_dmtec](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	PCB Mounting Orientation	Vertical
	Shrouded	Yes
	Row-to-Row Spacing	2.54 mm [.1 in]
	Connector Style	Plug
	Profile	Low
	Applies To	Printed Circuit Board
	Product Type	Connector
	Board Standoff	Without
	Connector Type	Header
	Connector System	Wire-to-Board
Ejection Latches	Without	
<hr/>		
Configuration Features	Number of Positions	26
	Number of Rows	2
<hr/>		
Electrical Characteristics	Operating Voltage (VAC)	250
	Insulation Resistance (MΩ)	1000 – 5000
<hr/>		
Body Features	Post Size	.64 mm [.025 in]
	Header Type	Pin Header
	Daisy Chain	With
<hr/>		
Contact Features	Contact Mating Area Plating Material	Gold
	Contact Shape	Square
	Solder Tail Contact Plating Material	Tin over Nickel
	Contact Current Rating (A)	1
	Contact Base Material	Phosphor Bronze
	Contact Mating Area Plating Thickness (µin)	30
	Contact Type	Pin
	Contact Termination Area Plating Material	Tin
	Contact Termination Area Plating Thickness	2.54 µm [100 µin]
<hr/>		
Termination Features	Termination Method to PC Board	Through Hole
	Termination Post Length	2.6 mm [.102 in]
<hr/>		
Mechanical Attachment	PCB Mount Retention	Without
	Mating Alignment Type	Center

Mating Connector Lock	Without
Mating Alignment	With
Polarization	With
Panel Mount Retention	Without
Mating Retention	With
PCB Mount Alignment	Without

Housing Features	Centerline	2.54 mm [.1 in]
	Housing Color	Blue
	Housing Style	4-Sided
	Housing Entry Style	Top
	Housing Material	PBT

Dimensions	Height	8.89 mm [.35 in]
	Length	40.64 mm [1.6 in]
	Shrouded End Dimension	3.81 mm [.15 in]

Usage Conditions	Temperature Rating	High
	Operating Temperature Range (°C)	-65 – 105

Operation/Application	For Use With	AMP-Latch Receptacle
-----------------------	--------------	-----------------------------

Industry Standards	UL Flammability Rating	UL 94V-0
--------------------	------------------------	-----------------

Packaging Features	Packaging Method	Package
	Packaging Quantity	50

Product Compliance

[Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

Products - 11 Results

[View All](#)

Compare 0/10 

Relation Type 

RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)



PRODUCT - MATING PRODUCTS

Connectors - Ribbon Cable Connectors
AMP-LATCH | AMP-LATCH - NOVO

**26 NOVO MIL/CTR 15DP,
LEAD FREE - 1658621-6**

TE INTERNAL NUMBER: 1658621-6

✓ Active

Always EU RoHS/ELV Compliant

Centerline **2.54 mm**

PCB Mount Retention **Without**

PCB Mounting Orientation

Vertical

Termination Method to PC Board

Through Hole - Solder

Termination Method to

Wire/Cable **Insulation**

Displacement Crimp (IDC)



PRODUCT - MATING PRODUCTS

Connectors - Ribbon Connector Accessories
AMP-LATCH | AMP-LATCH - NOVO

**026 STRAIN RELIEF A-L
RCPT - 499252-3**

TE INTERNAL NUMBER: 499252-3
ALIAS ID: 1108432

✓ Active

Always EU RoHS/ELV Compliant

Accessory Type **Strain Relief**




RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)



PRODUCT - MATING PRODUCTS

Connectors - Ribbon Connector Accessories
AMP-LATCH | AMP-LATCH - NOVO

**609-2631HD=FSKT IDC S
26 SR - 1-1437021-2**


TE INTERNAL NUMBER: 1-1437021-2
ALIAS ID: 609-2631HD

✓ Active

Always EU RoHS/ELV Compliant

Accessory Type **Strain Relief**

Number of Positions **26**



PRODUCT - MATING PRODUCTS

Connectors - Ribbon Cable Connectors
AMP-LATCH | AMP-LATCH - NOVO

**609-2630LF FEM SOCKET,
LEAD FREE - 1-1658526-5**

TE INTERNAL NUMBER: 1-1658526-5

✓ Active

Always EU RoHS/ELV Compliant

Number of Positions **26**

Connector Style **Receptacle**



RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)



PRODUCT - MATING PRODUCTS

Connectors - Ribbon Cable Connectors
AMP-LATCH | AMP-LATCH - NOVO

26 NOVO MIL 30DP,

Always EU RoHS/ELV Compliant

Centerline **2.54 mm**





LEAD FREE - 1658623-6

TE INTERNAL NUMBER: 1658623-6

✓ Active

PCB Mount Retention **Without**

PCB Mounting Orientation

Vertical

Termination Method to PC Board

Through Hole - Solder

Termination Method to

Wire/Cable **Insulation**

Displacement Crimp (IDC)

PRODUCT - MATING PRODUCTS



Connectors - Ribbon Connector Accessories
AMP-LATCH | AMP-LATCH - NOVO

026 STRAIN RELIEF A-L RCPT - 499252-3

TE INTERNAL NUMBER: 499252-3
ALIAS ID: 1108432

✓ Active

Always EU RoHS/ELV Compliant

Accessory Type **Strain Relief**

