




RIBBON CABLE CONNECTORS



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

MICRO-MATCH FTE,20P

[Micro-MaTch](#) | [Micro-MaTch Industrial](#)

2-338068-0

TE Internal Number: 2-338068-0

Always EU RoHS/ELV Compliant

Centerline **1.27 mm [.05 in]**

PCB Mount Retention **With**

PCB Mount Retention Type **Kink**

PCB Mounting Orientation **Vertical**

Termination Method to PC Board **Through Hole**

Product Drawings

[CONNECTOR, FEMALE-ON-BOARD TOP-ENTRY, THRU-HOLE,WITH LATCHES,Micro-Match](#)

PDF
English

CAD Files

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

[Customer View Model](#)

2D_DXF.ZIP
English

[3D PDF](#)

PDF
English

Catalog Pages/Data Sheets

[Micro-MaTch Catalog](#)

PDF
English

[Centerline Micro-Match Connector Series](#)

PDF
English

Product Specifications

Product Specification

[Amp Micro-Match Miniature Connector Assembly](#)

PDF
English

Qualification Test Report

[Test Report Lead-Free Wave Soldering-Heat \(Wave-Solder Connectors\)](#)

PDF
English

Product Type Features	PCB Mounting Orientation	Vertical
	Shrouded	Yes
	Connector Style	Receptacle
	Profile	Standard
	Applies To	Printed Circuit Board
	Product Type	Connector
	Board Standoff	Without
	Connector Type	Connector Assembly
	Connector System	Board-to-Board
Ejection Latches	Without	
Configuration Features	Number of Positions	20
Electrical Characteristics	Insulation Resistance (M Ω)	1000
	Operating Voltage (VDC)	100
Body Features	Header Type	Pin Header
	Daisy Chain	Without
Contact Features	Contact Mating Area Plating Material	Tin over Nickel
	Contact Design	Dual Beam
	Vacuum Tape	Without
	Contact Transmits (Typical)	Signal (Data)
	Solder Tail Contact Plating Material	Tin over Nickel
	Contact Current Rating (A)	1.5
	Contact Base Material	Phosphor Bronze
	Contact Type	Pin
	Contact Termination Area Plating Material	Tin
Termination Features	Termination Method to PC Board	Through Hole
	Termination Post Length	3.1 mm [.122 in]
Mechanical Attachment	PCB Mount Retention	With
	PCB Mount Retention Type	Kink
	Mating Connector Lock	With
	Mating Retention Type	Locking Latch

Mating Alignment	Without
Polarization	Without
Panel Mount Retention	Without
Mating Retention	Without
PCB Mount Alignment	Without

Housing Features	Centerline	1.27 mm [.05 in]
	Housing Color	Red
	Housing Entry Style	Top
	Housing Material	Polyester - GF

Dimensions	Height	4 mm [.16 in]
	Length	30 mm [1.18 in]
	PCB Thickness (Recommended) (mm)	1.6

Usage Conditions	Operating Temperature Range (°C)	-40 – 105
------------------	----------------------------------	------------------





Industry Standards	UL Flammability Rating	UL 94V-0
--------------------	------------------------	-----------------

Packaging Features	Packaging Method	Reel
	Packaging Quantity	2500

Product Compliance [Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

 <p>.140 DIA SOCKET 925663-1</p> <p>Save to List Find Similar Products</p>	<p>RIBBON CABLE CONNECTORS</p>  <p>MICRO-MATCH FTE, 12P 1-338068-2</p> <p>Save to List Find Similar Products</p>	<p>WIRE-TO-BOARD HEADERS & RECEPTACLES</p>  <p>09P MTA100 HDR ASSY SQ STR POL 640454-9</p> <p>Save to List Find Similar Products</p>	<p>BOARD-TO-BOARD HEADERS & RECEPTACLES</p>  <p>0.8FH, P08H.5, 140, 08/Sn, TU 5179031-6</p> <p>Save to List Find Similar Products</p>
--	--	--	---

Products - 13 Results

[View All](#)

[Compare 0/10](#)

Relation Type ▼

RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

PRODUCT - MATING PRODUCTS



Connectors - Ribbon Cable Connectors
Micro-MaTch I Micro-MaTch Industrial

**MICROM. MOB SMD
CON - 2-338728-0**

TE INTERNAL NUMBER: 2-338728-0

✓ Active

Always EU RoHS/ELV Compliant

Centerline **1.27 mm**

PCB Mount Retention **Without**

PCB Mounting Orientation

Vertical

Termination Method to PC Board

Surface Mount

Shrouded **Yes**



RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

PRODUCT - MATING PRODUCTS



Connectors - Ribbon Cable Connectors
Micro-MaTch I Micro-MaTch Industrial

**20P.MICRO-MATCH
MOB - 2-215464-0**

TE INTERNAL NUMBER: 2-215464-0

✓ Active

Always EU RoHS/ELV Compliant

Centerline **1.27 mm**

PCB Mount Retention **With**

PCB Mount Retention Type **Kink**

PCB Mounting Orientation

Vertical

Termination Method to PC Board

Through Hole



RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

PRODUCT - MATING PRODUCTS



Connectors - Ribbon Cable Connectors
Micro-MaTch I Micro-MaTch Industrial

**MICRO-MATCH
COSIHSG - 2-338095-0**

TE INTERNAL NUMBER: 2-338095-0

✓ Active

Always EU RoHS/ELV Compliant

Centerline **1.27 mm**

PCB Mount Retention **Without**

PCB Mounting Orientation

Vertical

Termination Method to PC Board

Through Hole - Solder



