



QUICK DISCONNECTS



TE CONNECTIVITY (TE)

110 ULTRA-FAST RCPT 22-18 TPBR

Ultra-Fast | 110

2-520080-2

TE Internal Number: 2-520080-2

Always EU RoHS/ELV Compliant

Mating Tab Width (mm) **2.79, 3.18**

Mating Tab Width (in) **.125**

Mating Tab Thickness **.41 mm [.016 in]**

Wire Insulation Diameter (Max) **3.05 mm [.12 in]**

Wire Size (AWG) **22 – 18**

Wire Size (mm?) **.32 – .82**

Active

PRODUCT DRAWING
English

3D PDF

Product Drawings

[RECEPTACLE ASSY,ULTRA-FAST, .110/.125 SERIES, 22-18AWG](#)

PDF
English

CAD Files

[3D PDF](#)

PDF
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

[Customer View Model](#)

2D_DXF.ZIP
English

Catalog Pages/Data Sheets

[Ultra-Fast And Ultra Fast Plus](#)

PDF
English

Product Specifications

Product Specification

[Ultra-Fast Fully Insulated FASTON Receptacle Terminals](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_2-520080-2_05172013630_dmtec](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Wire Stop	Yes
	Disconnect Type	Quick Disconnect Pin
	FASTON	Yes
	Wire/Cable Composition	Stranded
	Wire/Cable Type	Discrete Wire
	Insulated	Yes
	Insulated Wire Support	Yes
	Support Style	Insulation Support
	Applies To	Wire/Cable
Configuration Features	Paired	No
	Terminal Angle	Straight
Electrical Characteristics	Voltage (Max) (V)	600
Body Features	Plating Material	Tin
	Fully Insulated	Yes
Contact Features	Terminal Orientation	Straight
	Contact Plating Material	Tin
Termination Features	Crimp Type	F-Crimp
Dimensions	Mating Tab Width (mm)	2.79, 3.18
	Mating Tab Width (in)	.125
	Mating Tab Thickness	.41 mm [.016 in]
	Wire Insulation Diameter (Max)	3.05 mm [.12 in]
	Wire Size (AWG)	22 – 18
	Wire Size (mm ²)	.32 – .82
	Overall Length	18.702 mm [.735 in]
Usage Conditions	Operating Temperature Range (°C)	105
Industry Standards	UL Rating	Listed
	UL Flammability Rating	UL 94V-2

Packaging Features	Packaging Method	Reel
	Packaging Quantity	3000
Other	Barrel Color	Red

Product Compliance [Statement of Compliance PDF](#)
[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

CRIMP QUICK DISCONNECTS	CRIMP RINGS & SPADES	RIBBON CABLE CONNECTORS	MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES
<p>110 FAST REC 22-18 010PTPBR 61459-1</p> <p>Save to List Find Similar Products</p>	<p>TERMINAL R 90 DEG PG 8 10 55654-1</p> <p>Save to List Find Similar Products</p>	<p>A/L UNIV HDR 34P VERT LG LAT B 2-5499206-8</p> <p>Save to List Find Similar Products</p>	<p>16 MODII HDR DRRA 3/4SHRD LF 5-103164-6</p> <p>Save to List Find Similar Products</p>

Products - 2 Results

[View All](#)

[Compare 0/10](#)

Relation Type ▼

RELATIONSHIP

Toolings
Tooling

[See All Toolings](#)

PRODUCT - TOOLINGS



Application Tooling - OCEAN Applicators
AMP
OC-AT-S-FA-176D-001-0088 - 2151698-2
 TE INTERNAL NUMBER: 2151698-2

✓ Active

Not in Scope for EU RoHS/ELV Compliance

Region **Worldwide**

Tool Type **Applicator**

Spare Parts Tooling **No**

Applicator Style **OCEAN - Atlantic**

Applicator Feed Style **Side Feed**

RELATIONSHIP

PRODUCT - TOOLINGS



Application Tooling - OCEAN Applicators
AMP

OC-176D- CRIMPTOOLINGKIT - 7-2151698-7

TE INTERNAL NUMBER: 7-2151698-7

✓ Active

Not in Scope for EU RoHS/ELV
Compliance

Region **Worldwide**

Tool Type **Applicator**

Spare Parts Tooling **Yes**

Spare Parts Tool Type **Spare
Parts Kit**

