



QUICK DISCONNECTS



TE CONNECTIVITY (TE)

ULTRAFAST 187 ASSY REC 22-18 TPBR LP

Ultra-Fast | 187

2-520194-2

TE Internal Number: 2-520194-2

Alias ID: 110240

Always EU RoHS/ELV Compliant

Mating Tab Width **4.75 mm [.187 in]**

Mating Tab Thickness **.81 mm [.032 in]**

Wire Insulation Diameter (Max) **3.43 mm [.135 in]**

Wire Size (AWG) **22 – 18**

Wire Size (mm²) **.32 – .82**

✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

Product Drawings

[RECEPTACLE ASSY,ULTRA-FAST, LOOSE PIECE,.187 SERIES,22-18 AWG](#)

PDF
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

[3D PDF](#)

PDF
English

Catalog Pages/Data Sheets

[Ultra-Fast And Ultra Fast Plus](#)

PDF
English

Product Specifications

Product Specification

[Ultra-Fast Fully Insulated FASTON Receptacle Terminals](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_2-520194-2_0918201532_dmtec](#)

PDF
English

Product Type Features	Wire Stop	Yes
	Disconnect Type	Quick Disconnect Pin
	FASTON	Yes
	Wire/Cable Composition	Stranded
	Wire/Cable Type	Discrete Wire
	Insulated	Yes
	Insulated Wire Support	Yes
	Support Style	Insulation Support
	Applies To	Wire/Cable
Configuration Features	Paired	No
	Terminal Angle	Straight
Electrical Characteristics	Voltage (Max) (V)	600
Body Features	Plating Material	Tin
	Fully Insulated	Yes
Contact Features	Terminal Orientation	Straight
	Contact Plating Material	Tin
Termination Features	Crimp Type	F-Crimp
Dimensions	Mating Tab Width	4.75 mm [.187 in]
	Mating Tab Thickness	.81 mm [.032 in]
	Wire Insulation Diameter (Max)	3.43 mm [.135 in]
	Wire Size (AWG)	22 – 18
	Wire Size (mm ²)	.32 – .82
	Overall Length	21.755 mm [.855 in]
Usage Conditions	Operating Temperature Range (°C)	105
Industry Standards	UL Rating	Listed
	UL Flammability Rating	UL 94V-2
Packaging Features	Packaging Method	Loose Piece

Packaging Quantity

1000

Other

Barrel Color

Red

Product Compliance

[Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

POTENTIOMETERS	CHASSIS PANEL MOUNT RESISTORS	IDC D-SUB CONNECTORS	WIRE-TO-BOARD CONNECTOR HOUSINGS
17P/PC 470KA 6X19FL SPDT PP 17PCSA474MC19P	HSA50 15K 3% HSA5015KE	KIT, RCPT, 15P, HDE, SHLD ENCLSRE 1-747945-5	5 POS EP 2.5 HSG, GLOW WIRE 1744417-5
Save to List Find Similar Products	Save to List Find Similar Products	Save to List Find Similar Products	Save to List Find Similar Products