



QUICK DISCONNECTS



TE CONNECTIVITY (TE)

ULTRAFAST 250 ASSY REC 22-18 TPBR LP

Ultra-Fast | 250

2-520264-2

TE Internal Number: 2-520264-2
Alias ID: AMPS-2-0520264-2, CN2878-000

Always EU RoHS/ELV Compliant

Mating Tab Width **6.35 mm [.25 in]**

Mating Tab Thickness **.81 mm [.032 in]**

Wire Insulation Diameter (Max) **5.84 mm [.23 in]**

Wire Size (AWG) **22 – 18**

Wire Size (mm²) **.32 – .82**

✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

Product Drawings

[RECEPTACLE ASSY,ULTRA-FAST, LOOSE PIECE,,250 SERIES,22-18 AWG](#)

PDF
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

[3D PDF](#)

PDF
English

Catalog Pages/Data Sheets

[Ultra-Fast And Ultra Fast Plus](#)

PDF
English

Product Specifications

Product Specification

[Ultra-Fast Fully Insulated FASTON Receptacle Terminals](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_2-520264-2_04212015451_dmtec](#)

PDF
English

| | | |
|----------------------------|----------------------------------|------------------------------|
| Product Type Features | Wire Stop | Yes |
| | Disconnect Type | Quick Disconnect Pin |
| | FASTON | Yes |
| | Wire/Cable Composition | Stranded |
| | Wire/Cable Type | Discrete Wire |
| | Insulated | Yes |
| | Insulated Wire Support | Yes |
| | Support Style | Insulation Support |
| Applies To | Wire/Cable | |
| Configuration Features | Paired | No |
| | Terminal Angle | Straight |
| Electrical Characteristics | Voltage (Max) (V) | 600 |
| Body Features | Plating Material | Tin |
| | Fully Insulated | Yes |
| Contact Features | Terminal Orientation | Straight |
| | Contact Plating Material | Tin |
| Termination Features | Crimp Type | F-Crimp |
| Dimensions | Mating Tab Width | 6.35 mm [.25 in] |
| | Mating Tab Thickness | .81 mm [.032 in] |
| | Wire Insulation Diameter (Max) | 5.84 mm [.23 in] |
| | Wire Size (AWG) | 22 – 18 |
| | Wire Size (mm ²) | .32 – .82 |
| | Overall Length | 23.791 mm [.935 in] |
| Usage Conditions | Operating Temperature Range (°C) | 105 |
| Industry Standards | UL Rating | Listed |
| | UL Flammability Rating | UL 94V-2 |
| Packaging Features | Packaging Method | Loose Piece |

Packaging Quantity

1000

Other

Barrel Color





Red

Product Compliance

[Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

| RECTANGULAR POWER CONNECTORS | HEAT SHRINK TUBING | CRIMP QUICK DISCONNECTS | CRIMP RINGS & SPADES |
|--|--|--|--|
|  <p>06P UMNLI II IN-LNE PLUG HSG KIT 770020-1</p> |  <p>RNF-100-MINI-SPL-1/8-BK RNF-100-MINI-SPL-1/8-BK</p> |  <p>250 ULTRA-FAST FLAG 16-14 TPBR 3-521013-2</p> |  <p>TERMINAL, PIDG R 16-14 1/4 320563</p> |
| <p>Save to List Find Similar Products</p> | <p>Save to List Find Similar Products</p> | <p>Save to List Find Similar Products</p> | <p>Save to List Find Similar Products</p> |