



QUICK DISCONNECTS



TE CONNECTIVITY (TE)

ULTRAFAST 187 ASSY FLAG REC 22-18 TPBR

Ultra-Fast | 187

2-520334-2

TE Internal Number: 2-520334-2
 Alias ID: 038-3990-00

Always EU RoHS/ELV Compliant

Mating Tab Width **4.75 mm [.187 in]**

Mating Tab Thickness **.51 mm [.02 in]**

Wire Insulation Diameter (Max) **4.19 mm [.165 in]**

Wire Size (AWG) **22 – 18**

Wire Size (mm²) **.3 – .9**

✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

Product Drawings

[RECEPTACLE ASSEMBLY,ULTRA-FAST FLAG, 4.75 \[.187\] SERIES](#)

PDF
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

[3D PDF](#)

PDF
English

Catalog Pages/Data Sheets

[Ultra-Fast And Ultra Fast Plus](#)

PDF
English

Product Specifications

Product Specification

[Ultra-Fast Fully Insulated FASTON Receptacle Terminals](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_2-520334-2_07022013617_dmtec](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Disconnect Type	Quick Disconnect Pin
	FASTON	Yes
	Wire/Cable Composition	Stranded
	Wire/Cable Type	Discrete Wire
	Insulated	Yes
	Insulated Wire Support	Yes
	Support Style	Insulation Support
	Applies To	Wire/Cable
Configuration Features	Paired	No
	Terminal Angle	90°
Electrical Characteristics	Voltage (Max) (V)	600
Body Features	Plating Material	Tin
	Fully Insulated	Yes
Contact Features	Terminal Orientation	Flag
	Contact Plating Material	Tin
Termination Features	Crimp Type	Tab-Lok
Dimensions	Mating Tab Width	4.75 mm [.187 in]
	Mating Tab Thickness	.51 mm [.02 in]
	Wire Insulation Diameter (Max)	4.19 mm [.165 in]
	Wire Size (AWG)	22 – 18
	Wire Size (mm ²)	.3 – .9
	Overall Length	13.08 mm [.515 in]
Usage Conditions	Operating Temperature Range (°C)	105
Industry Standards	UL Rating	Listed
	UL Flammability Rating	UL 94V-2
Packaging Features	Packaging Method	Reel
	Packaging Quantity	2200

Other

Barrel Color

Red

Product Compliance

[Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

WIRE-TO-BOARD HEADERS & RECEPTACLES	AUTOMOTIVE, TRUCK, BUS, & OFF-ROAD HEADERS	RECTANGULAR POWER CONNECTORS	AUTOMOTIVE, TRUCK, BUS, & OFF-ROAD HEADERS
02 MTE HDR SRST LATCH W/HLDWN 5-104809-1	14 POS AMPSEAL VERTICAL HDG 776261-1	03P .156 MNL CAP HSG 794413-1	14P AMPSEAL VERT ASSY 1-776261-1
Save to List Find Similar Products	Save to List Find Similar Products	Save to List Find Similar Products	Save to List Find Similar Products