



# QUICK DISCONNECTS



TE CONNECTIVITY (TE)

## 250 ULTRA-FAST PLUS 22-18 TPBR

Ultra-Fast | 250

2-520407-2

TE Internal Number: 2-520407-2

Alias ID: 668-1004-02, F57023-000, HUB-FULLINSUL-22-18FM

Always EU RoHS/ELV Compliant

Mating Tab Width **6.35 mm [ .25 in ]**

Mating Tab Thickness **.81 mm [ .032 in ]**

Wire Insulation Diameter **1.52 – 3.42 mm [ .06 – .135 in ]**

Wire Size (AWG) **22 – 18**

Wire Size (mm<sup>2</sup>) **.32 – .82**

Active

PRODUCT DRAWING  
English

3D PDF

### Product Drawings

[RECEPTACLE ASSY,ULTRA-FAST PLUS, LOOSE PIECE,,250 SERIES,22-18 AWG](#)

PDF  
English

### CAD Files

[Customer View Model](#)

3D\_IGS.ZIP  
English

[Customer View Model](#)

3D\_STP.ZIP  
English

[Customer View Model](#)

2D\_DXF.ZIP  
English

[3D PDF](#)

PDF  
English

### Catalog Pages/Data Sheets

[Ultra-Fast And Ultra Fast Plus](#)

PDF  
English

### Product Environmental Compliance

TE Material Declaration

[MD\\_2-520407-2\\_01082015170\\_dmtec](#)

PDF  
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

### Product Type Features

Wire Stop

Yes

Disconnect Type

Quick Disconnect Pin

Custom

Yes

FUNCTION RES

Wire/Cable Composition **Stranded**

Wire/Cable Type **Discrete Wire**

Insulated **Yes**

Insulated Wire Support **Yes**

Support Style **Insulation Support**

Applies To **Wire/Cable**

---

Configuration Features Paired **No**

Terminal Angle **Straight**

---

Electrical Characteristics Voltage (Max) (V) **600**

---

Body Features Plating Material **Tin**

Fully Insulated **Yes**

---

Contact Features Terminal Orientation **Straight**

Contact Plating Material **Tin**

---

Termination Features Crimp Type **F-Crimp**

---

Dimensions Mating Tab Width **6.35 mm [ .25 in ]**

Mating Tab Thickness **.81 mm [ .032 in ]**

Wire Insulation Diameter **1.52 – 3.42 mm [ .06 – .135 in ]**

Wire Size (AWG) **22 – 18**

Wire Size (mm<sup>2</sup>) **.32 – .82**

Overall Length **21.755 mm [ .855 in ]**

---

Usage Conditions Operating Temperature Range (°C) **105**

---

Industry Standards UL Rating **Listed**

UL Flammability Rating **UL 94V-2**

---

Packaging Features Packaging Method **Loose Piece**

Packaging Quantity **1000**

---

Other Barrel Color **Red**

---

Product Compliance

[Statement of Compliance](#)  
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)